

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 22624

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lukens Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 25, T26S, R25E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

JUN 15 1982

2. NAME OF OPERATOR

Exxon Corporation

O. C. D.

3. ADDRESS OF OPERATOR

ARTESIA, OFFICE

Box 1600 Midland, TX 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

990' FSL and 1980' FEL of Section

14. PERMIT NO.

30-015-23423

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3584 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Set blanking plug at 10,290'. Spot 25 sx plug at 10,240' - could not find plug.
Spot 25 sx plug at 10,240' - tagged plug at 10,130'.
2. Cut 5½" csg at 6647 and pulled. Set 70 sx cmt. plug at 6701, with top of plug at 6360', set 60 sx. plug at 5150, with top of plug at 5100'. Spot 50 sx plug at 5100' - top of plug at 4900'. Spot 50 sx plug at 416', with 10 sx cmt plug at surface.
3. Installed dry hole marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

S. H. L...

TITLE Sr. Administrator

DATE 5/6/81

(This space for Federal or State Office Use)

APPROVED (Orig. Sgd.) PETER W. CHESTER
CONDITIONS OF APPROVAL, IF ANY:

JUN 11 1982

FOR

JAMES A. GILLHAM *See Instructions on Reverse Side
DISTRICT SUPERVISOR