



UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY  
P. O. Drawer U  
Artesia, New Mexico 88210

RECEIVED

AUG 18 1980

O. C. D.  
ARTESIA, OFFICE

August 4, 1980

Amoco Production Company  
P. O. Box 68  
Hobbs, New Mexico 88240

Gentlemen:

AMOCO PRODUCTION COMPANY  
Fed "BQ" No. 1  
1980 FSL 660 FEL Sec. 26 T.26S R.25E  
Eddy County Lease No. NM-22625

Above Data Required on Well Sign

Your APPLICATION FOR PERMIT TO DRILL the above-described well to a depth of 10,200 feet to test the Morrow is hereby approved subject to compliance with the OIL AND GAS OPERATING REGULATIONS (30 CFR 221) and the following conditions:

1. Drilling operations authorized are subject to compliance with the attached General Requirements for Oil and Gas Operations on Federal Leases, dated July 1, 1978.
2. Prior to commencing construction of road, pad, or other associated developments, operator will provide the dirt contractor with a copy of the Surface Use Plan and these Conditions of Approval including the attached General Requirements.
3. All access roads will be limited to a 12 foot wide driving surface, excluding turnarounds. Surface disturbance associated with road construction will be limited to 20 feet in width.
4. Submit a Daily Report of Operations from spud date until the well is completed and the Well Completion Report (form 9-330) is filed. The report should not be less than 8" x 5" in size and each page should identify the well.
5. All permanent above-ground structures and equipment shall be painted in accordance with the attached Painting Guidelines. The color used should simulate Sandstone Brown (Federal Standard No. 595A, color 20318 or 30318) or Amoco's Standard Gray color.
6. Before drilling below the 9-5/8" casing, the blowout preventer assembly will consist of a minimum of one annular type and two ram type preventers.
7. A kelly cock will be installed and maintained in operable condition.