

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
Amoco Production Company  
3. ADDRESS OF OPERATOR  
P. O. Box 68 Hobbs, NM 88240  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL X 660' FEL, Sec. 26  
AT TOP PROD. INTERVAL: (Unit I, NE/4, NE/4)  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE  
NM-22625  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Federal BQ  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME  
Morrow  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
26-26-25  
12. COUNTY OR PARISH  
Eddy  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3636.3 GL

RECEIVED

SEP 24 1980

O.C.D.  
ARTESIA, OFFICE

(NOTE: Report results of multiple completion or zone changes on Form 9-330.)

U.S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

958'  
Drilled to a TD of 5027' and ran 40# N80 casing set at 5027'. Cemented with 1450 SX Lite cement with additives and with 200 SX Class C Neat cement. Plugged down at 12:30 p.m. 9-30-80. Cement did not circulate. Ran temp survey. Top of cement at approx. 1250'. Ran a 1" down annulus X tagged cement at 1188'. Pulled up to 1174' and cemented with 400 SX Class C Neat cement. WOC 22 hr. Tested casing with 1000# for 30 min. Test OK. Reduced hole to 8-3/4" and resumed drilling.

0+5-USGS, H 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou  
1-Getty 1-Hudson X Hudson

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Benton Green TITLE Ast. Adm. Analyst DATE 9-17-80

APPROVED BY R. Chester TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD  
SEP 22 1980  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side