




ADDITIONS-DELETIONS-CHARGES SPECIFY

The blowout preventer assembly shall consist of one single type blind ram preventer and one single type pipe ram preventer, both hydraulically operated, a Hydril® GK® preventer, a rotating blowout preventer, valve ducks and seal connections, as illustrated. If a tapered drill string is used, a ram preventer must be provided for each size of drill pipe. Casing and tubing rams to fit the preventers are to be available as needed. If correct in size, the flanged outlets of the ram preventer may be used for connecting to the 4-inch I.O. choke flow line and 4-inch I.D. relief line, except when air or gas drilling. All preventer connections are to be open-face flanged.

Minimum operating equipment for the prevention and hydraulically operated valves shall be as follows: (1) Multiple pumps, driven by a continuous source of power, capable of fluid charging the total accumulator volume from the nitrogen presurge pressure to its rated pressure within _____ minutes. Also, the pumps are to be connected to the recharge of nitrogen of not less than 750 PSI and connected so as to receive the aforementioned fluid charge. With _____ must be sufficient to close all the pressure-operated devices simultaneously within _____ seconds after closure, accumulator fluid volume at least _____ percent of the original. (3) When required, an additional source of _____ shall be additional pumps operated by separate power and equal in performance capabilities.

The closing manifold and remote closing manifold shall have a separate control for each pressure-operated device. Controls are to be labeled, with control handles indicating open and closed positions. A pressure reducer and regulator must be provided for operating the Hydral preventer. When requested, a second pressure reducer shall be available to limit operating fluid pressures to ten percent. Gulf Legion No. 38 hydraulic oil, an equivalent or better, is to be used as the fluid to operate the hydraulic equipment.

The choke manifold, choke flow line, relief line, and choke lines are to be supported by metal stands and adequately anchored. The choke flow line, relief line, and choke lines shall be constructed as straight as possible and without sharp bends. Easy and safe access is to be maintained to the choke manifold. If deemed necessary, walkways shall be erected in and around the manifold. All valves are to be selected for operation in the presence of oil, gas, and drilling fluids. The choke flow line valves and relief line valves connected to the drilling pool and all run type preventers must be equipped with stem extensions, unvalved joints if needed, and hand wheels which are to extend beyond the edge of the derrick substructure. All other valves are to be equipped with handles.

It To include derick floor mounted controls.