## UNITED TATES HE INTERIOR DEPARTMENT (

N.M. Oil Cons. D.

FORM APPROVED

0151

**BUREAU OF LAND MANAGEMENT** 

Q11 C 1et Stroot 5. Lease Serial No.

_	OMI	3 MO.	1004	~VI.	ມ
n	Expires	Nove	mber	30,	20

SUNDRY NOTICES AND REPORTS ON WELLS.  Do not use this form for proposals to drill or to referrite Sita, abandoned well. Use Form 3160-3 (APD) for such proposals.	NM 8821
---	---------

M 67106 H fibriah, Allottee or Tribe Name

					<u> </u>	
_		RIPLICATE - Oth	er instructions (	on reverse side 31	7. If Unit or CA/Agreement, Name and/or No	2.
	Type of Well Oil Well Gas Well	Other		- <del>                                     </del>	8. Well Name and No. Sotol A Federal 1	
	Name of Operator Ricks Exploratio Address	n, Inc.	3b. Pho	ne No. (include area code)	9. API Well No. 30-015-23459	
	210 Park Avenue  Location of Well (Footage, Sec		C, OK 73102	405/516-11009	10. Field and Pool, or Exploratory Area Cotton Draw (Atoka) Gas	
••	F 1980' FNL; 198 Section 12-24S-3	O' FWL		( crarery	11. County or Parish, State  Eddy County	
	12. CHECK AF	PROPRIATE BO	X(ES) TO INDICA	TE NATURE OF NOTION	CE, REPORT, OR OTHER DATA	
	TYPE OF SUBMISSION			TYPE OF ACTIO	N	
_		Acidize	Deeper Deeper	Productio	n (Start/Resume) Water Shut-Off	

(See 140tice of mienr	Alter Casing	i riaciure i reat	L Reciamation	ч	wen megnty
Subsequent Report	Casing Repair	New Construction	Recomplete		Other
	Change Plans	Plug and Abandon	Temporarily Abandon		<del> </del>
Final Abandonment Notice	Convert to Injection	Plug Back			
Attach the Bond under which the	ectionally or recomplete horizon he work will be performed or p rolved operations. If the operat nal Abandonment Notices shall	tally, give subsurface location rovide the Bond No. on file ion results in a multiple com-	mated starting date of any proposes and measured and true vertical with BLM/BIA. Required subsepletion or recompletion in a new rements, including reclamation, h	quent repr quent repr interval, a	t all pertinent markers and zones. orts shall be filed within 30 days i Form 3160-4 shall be filed once

CIBP @ 7100' capped with 35' cement. Cement plug in 9-5/8" csg and 13-3/8" csg from 4465' to 4360'. Surface cement plug from GL - 50' in 13-3/8" csg. Fill all intervals between plugs with 9 ppg mud. All csg cut off 3' below restored GL. Install dry hole marker.

Set Cement Plug F/2500-2600' Set Cement Plug F/610-710'-TAG

determined that the site is ready for final inspection.)

proved by OPIC SOO DAVIDE CO. ASS and the approval, if any, are attached. Approval of this notice does not the applicant holds legal or equitable title to those rights in the applicant to conduct operations thereon.	PETROLEUM ENGINEER Date	SEP 2 8 2000
THIS SPACE FOR I		
Signature Cindy & Coviden	Date 9/12/00	
Name (Printed/Typed)  Cindy L. Carden	Title Production Asssitant	

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.