

FILED COPY

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FWL X 1980 FEL, Sec. 35  
AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4)  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(other) Set intermediate casing

5. LEASE  
NM-17232

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Big Sinks Federal Unit O.C.D.

9. WELL NO. 1 ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME  
Wildcat Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
35-25-31

12. COUNTY OR PARISH Eddy 13. STATE NM

14. API NO.  
30 015 23491

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3350.3' RDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 8-22-81 ran 9-5/8", 53.5#, S-95, intermediate casing. Set at 12140'. Cemented first stage with 800 sacks of Lite containing .6% Halad-22 and 1/4#/sack of flocele. Tailed in with 300 sacks of Class H containing .6% Halad-22 and .4% CFR-2. Open DV tool set at 8319 and circulated for 4 hrs. Cemented second stage with 2000 sacks of Lite containing .4% Halad-22 and 1/4#/sack of flocele. Tailed in with 200 sacks of Class H containing .6% Halad-22 and 4% CFR-2. Reduced hole to 8-1/2" and resumed drilling.

0+4-USGS, A 1-Hou 1-Susp 1-W. Stafford, Hou 1-MDR  
1-Yates Pet. 1-Gulf 1-Mesa

Subsurface Safety Valve: Manu. and Type Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN TITLE A. Adm. Analyst DATE 8-31-81

NOV 9 1981

(This space for Federal or State office use)

APPROVED BY CONDITIONS OF APPROVAL IF ANY TITLE DATE

U.S. GEOLOGICAL SURVEY  
POSWELL, NEW MEXICO