1. oil well well other 8. FARM OR LEASE NAME ARTESIA, OFFIC 1. oil well well other 9. WELL NO. 9. WELL NO. 2. NAME OF OPERATOR 1 10. FIELD OR WILDCAT NAME Amoco Production Company 10. FIELD OR WILDCAT NAME 3. ADDRESS OF OPERATOR 11. SEC., T., R., M., OR BLK. AND SURVEY OR 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) N AT SURFACE: 660' FML X 1980' FEL, Sec. 35 AT TOTAL DEPTH: 12. COUNTY OR PARISH 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 30 015 23491 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3350.3 RDB	Artesia, NM 83210 Form 9-331	Form Approved.
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY RECEIVE MI 1/232 MI 1/232 MI 1/232 MI 1/232 MI 1/232 RECEIVE MI 1/232 Rec		
GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS JAN 2010 Colspan="2">JAN 2010 JAN 2010 <t< th=""><th></th><th></th></t<>		
JAN 21.19 SUNDRY NOTICES AND REPORTS ON WELLS Construction of proposations to different of plug basis to different different user form 3-331-6 for such proposations and means that a different different user form 3-331-6 for such proposations and means and proposations and proposations and means and proposations and preceived preprovemeation and properimeter andisproposation proposa	-	
SUNDRY NOTCES AND REPORTS ON WELLS 7. UNIT AGREEMENT NAME Octoor data form 3-312 Consumption properties Octoor properties 1. oil well gest Other 2. NAME OF OPERATOR AND OF LEASE NAME ARTESIA, OPFIN 3. ADDRESS OF OPERATOR	GEOLOGICAL SURVEI	
OB: not use this form for proposals to drift to deepen or plug back to a different well O. C. D. D. B: FARM OR LEASE NAME O. C. D. D. B: FARM OR LEASE NAME 1. oil B: Sinks Particle D. Sinks Particle <	SUNDRY NOTICES AND REPORTS ON WELLS	
I. oil well @ as well other ARTESIA.OFFI 1. oil well @ set @ other B: FARM OR LEASE NAME ARTESIA.OFFI 2. NAME OF OPERATOR II. Amoco Production Company II. 3. ADDRESS OF OPERATOR II. 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) Soc 58. Hobbs. NM 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) Soc 55. AND SURVEY OR AREA AT TOTAL DEPTH. II. SEC., T., R. M. OR BLK. AND SURVEY OR AREA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. Soc 25. 31 17. DESCRIBE FROPOSED OR OTHER DATA SUBSEQUENT REPORT, OF REPART, OR OTHER DATA III. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS Clearly state all pertinent details, and give pertinent details. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS Clearly state all pertinent details, and give subsurface locations and messured and true vertical depths for all markers and zones pertinent ot this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS Clearly state all pertinent details, and give subsurface locations and messured and true vertical depths for all markers and zones pertinent ot this work.)* 18. Interedo cating and true vertical depths for all markers and zones pertinent ot this work.)* 19. Other Index Interest Index I	(Do not use this form for proposals to drill or to deepen or plug back to a different	<u>O. C. D</u> .
Windle String All other 9. WELL NO. 2. NAME OF OPERATOR 1 Amoco Production Company 1 3. ADDRESS OF OPERATOR 1 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) 15. EFLD OR WILDCAT NAME MILCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) 15. EFLD OR WILDCAT NAME MILCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) 15. EFLD OR WILDCAT NAME MIL CATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) 13. STATE MILCAT DEPTH: 1 12. COUNTY OR PARISH 13. STATE 16. OFFECK APPROVAL DEPTH: 10. JAN 195. 23491 13. STATE 17. DESCRIBE FROPOSED OR COMPLETED OFENATIONS CLEARLY task all periment details, and give pertinent details, and give pertinent details, and give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 17. DESCRIBE PROPOSED OR COMPLETED OFENATIONS CLEART I. Well is difficiential details, and give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Drilled to TD of 15700'. Ran 4-1/2" N-80 13.5 1b/ft. There set at 15699' top of Timer 14403'. Cemented with 200 sacks Class H with 5 1bs. gilsonite per sack. WOC 18 hrs. Drilled out Casent to 14403'. Pressure tested casing to 1000 PSI for 30 min. Tested 0K. Rig released 1-10-82. No further report until move in completion unit. 0+6-USGS, R 1-Hou 1-Susp 1-W. Stafford, Hou	reservair. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME ARTESIA, OFFI
2. NAME OF OPERATOR 1 ABDCCS OF OPERATOR 10. FIELD OR WILDCAT NAME WildCat MOPTOW 1.0. FIELD OR WILDCAT NAME 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 11. SEC. T. R. M., OR BLK. AND SURVEY OR AREA 3. LOCKES OF OPERATOR 11. SEC. T. R. M., OR BLK. AND SURVEY OR AREA 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4) AT TOTAL DEPTH. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. 17. DEGONIT, OR OTHER DATA REQUEST FOR APPROPAL TO: SUBSEQUENT REPORT, OF TEST WATER SHUT-OFF BULL OF ALTER CASING WULTIPLE COMPLETE DORA COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including setmated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all matters and zones pertinent to this work." Drilled to TD of 15700'. Ran 4-1/2'' N-80 13.5 lb/ft. liner set at 15699' top of liner 14403'. Cemented with 200 sacks Class H with 5 lbs. gilsonite per sack. WOC 18 hrs. Drilled out cament to 14403'. Pressure tested casing to 1000 PSI for 30 min. Tested 0K. Rig released 1-10-82. No further report until move in completion unit. OH6-USGS, R 1-Hou 1-Susp 1-W. Stafford, Hou 1-DMF 1-Yates 1-Mesa 1-Gulf	1. oil gas wall W other	
Amoco Production Company 3. ADDRESS OF OPERATOR 0. FIELD OR WILDCAT NAME Wildcat Morrow P. O. Box 68, Hobbs, NM 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AT TOP ROD. INTERVAL: (Unit B, NW/4, NE/4) 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent detail		
A. DORRESS OF OPERATOR P. O. Box 68, Hobbs, NM 88240 P. O. Box 68, Hobbs, NM 88240 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 660' FML X 1980' FEL, Sec. 35 AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4) AT TOTAL DEFTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: REVEL PULL OR ALTER CASING MULTIPLE COMPLETE CHANCE ZONES ABANDON* Other Dot 15700'. Ran 4-1/2" N-80 13.5 1b/ft. liner set at 15699' COMPLET OF THE AGAIR TO D of 15700'. Ran 4-1/2" N-80 13.5 1b/ft. liner set at 15699' COM OF SIGN, R. 1-HOU Drilled to TD of 15700'. Ran 4-1/2" N-80 13.5 1b/ft. liner set at 15699' COM OF SI for 30 min. Tested OK. Rig released 1-10-82. No further report until move in completion unit. OH6-USGS, R 1-Hou 1-Susp I-Yates 1-MOL THECORE Corect REQUENT RECORD OF COMPLETE OFFERCION (or Federal or State office ure) Ft. 18. Hereby certify that the forgoing is true and correct sing to this work.)* Including estimated date of starting any p		10. FIELD OR WILDCAT NAME
P. O. Box 68, Hobbs, NM 88240 II. SEC. T, R. M., OR BLK. AND SURVEY OR 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AREA AT SURFACE: 660' FML X 1980' FEL, Sec. 35 AT TOP ROD. INTERVAL: (Unit B, NW/4, NE/4) 12. COUNTY OR PARISH 13. STATE Eddy NM 14. API NO. 30 015 23491 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3350.3 RDB REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT, OF: FEATURE TREAT SHOOT OR ACIDZE REPORT, OR THER CASING PULL OR ALTER CASING		Wildcat Morrow
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below) AT SURFACE: 660' FML X 1980' FEL, Sec. 35 AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4) AT TOTAL DEPTH: AREA 35-25-31 12. COUNTY OR PARISH 13. STATE Eddy NM 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA NM NM 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: HAA APP NO. 3350.3 RDB 30.015 23491 15. ELEVATIONS (FMDW DF, KDB, AND WD) 3350.3 RDB 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work. ⁺ 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work. ⁺ 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work. ⁺ 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated data. Set @ Se	P. O. Box 68, Hobbs, NM 88240	
AT SUPFACE: 660' FML X 1980' FEL, Sec. 35 AT TOTAL DEPTH: (Unit B, NW/4, NE/4) 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. 30 015 23491 17. DESCRIBE SHUT-OF	4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	
AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4) AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL AND 19 1925 Appendix of multiple completion or zone PULL OR ALTER CASING MULTIPLE COMPLETE (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Drilled to TD of 15700'. Ran 4-1/2" N-80 13.5 1b/ft. liner set at 15699' top of liner 14403'. Cemented with 200 sacks Class H with 5 1bs. gilsonite per sack. WOC 18 hrs. Drilled out cament to 14403'. Pressure tested casing to 1000 PSI for 30 min. Tested 0K. Rig released 1-10-82. No further report until move in completion unit. 0+6-USGS, R 1-Hou 1-Susp 1-W. Stafford, Hou 1-DMF 1-Yates 1-Mesa 1-Gulf Subsurface Safety Valve: Manu. and Type REST APPROVAL JAN*2 0 1982 1000 DATE DATE SATE ADD APPROVAL JAN*2 0 1982	Delow.)	
AT TOTAL DEPTH: 14. API NO. 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. 14. API NO. 30. O15 23491 15. ELEVATIONS (SHOW DF, KDB, AND WD) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS ULAW 1 9 (907E: Report results of multiple completion or zone chafte on Form 9-330.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Drilled to TD of 15700'. Ran 4-1/2'' N-80 13.5 1b/ft. liner set at 15699' top of liner 14403'. Cemented with 200 sacks Class H with 5 1bs. gilsonite per sack. W0C 18 hrs. Drilled out cament to 14403'. Pressure tested casing to 1000 PSI for 30 min. Tested 0K. Rig released 1-10-82. No further report until move in completion unit. 0+6-USGS, R 1-Hou 1-Susp 1-W. Stafford, Hou 1-DMF 1-Yates 1-Mesa 1-Gulf Subsurface Safety Valve: Manu. and Type Set @ F*. 18. I hereby certify that/the foregoing is true and correct SIGNED RCGER A. CHAP DRMNace for Federal or State office use) APPROVED BY TIT APPROVED BY TIT	AT TOP PROD. INTERVAL: (Unit B, NW/4, NE/4)	
REPORT, OR OTHER DATA 15. ELEVATIONS (SHOW DF, KDB, AND WD) 3350.3 RDB REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF TEST WATER SHUT-OFF	AT TOTAL DEPTH:	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: 3350.3 RDB FRACTURE TREAT		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF FRACTURE TREAT	REPORT, OR OTHER DATA	
TEST WATER SHUT-OFF	REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	<u>3350.3 RDB</u>
SHOOT OR ACIDIZE		The second s
REPAIR WELL		
PULL OR ALTER CASING		
CHANGE ZONES		
ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Drilled to TD of 15700'. Ran 4-1/2" N-80 13.5 1b/ft. liner set at 15699' top of liner 14403'. Cemented with 200 sacks Class H with 5 lbs. gilsonite per sack. WOC 18 hrs. Drilled out coment to 14403'. Pressure tested casing to 1000 PSI for 30 min. Tested 0K. Rig released 1-10-82. No further report until move in completion unit. 0+6-USGS, R 1-Hou 1-Susp 1-W. Stafford, Hou 1-DMF 1-Yates 1-Mesa 1-Gulf Subsurface Safety Valve: Manu. and Type Set @ Set @ State office use) ROGER A. CHAP MYN pace for Federal or State office use) ROGER A. CHAP MYN pace for Federal or State office use) ROGER A. CHAP MYN pace for Federal or State office use) PERPROVED BY CONDITIONS OF APPROVAL JAN 2 0 1982		a mark
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Drilled to TD of 15700'. Ran 4-1/2" N-80 13.5 lb/ft. liner set at 15699' top of liner 14403'. Cemented with 200 sacks Class H with 5 lbs. gilsonite per sack. WOC 18 hrs. Drilled out cament to 14403'. Pressure tested casing to 1000 PSI for 30 min. Tested OK. Rig released 1-10-82. No further report until move in completion unit. O+6-USGS, R 1-Hou 1-Susp 1-W. Stafford, Hou 1-DMF 1-Yates 1-Mesa 1-Gulf Subsurface Safety Valve: Manu. and Type	ABANDON*	Al 46 Altowns
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Drilled to TD of 15700'. Ran 4-1/2" N-80 13.5 1b/ft. liner set at 15699' top of liner 14403'. Cemented with 200 sacks Class H with 5 lbs. gilsonite per sack. WOC 18 hrs. Drilled out cament to 14403'. Pressure tested casing to 1000 PSI for 30 min. Tested OK. Rig released 1-10-82. No further report until move in completion unit. 0+6-USGS, R 1-Hou 1-Susp 1-W. Stafford, Hou 1-DMF 1-Yates 1-Mesa 1-Gulf Subsurface Safety Valve: Manu. and Type Set @ \$2. 18. I hereby certify that the foregoing is true and correct Signed RCGER A. CHAP BRANPAGE for Federal or State office use) Date Appenoved by RCGER A. CHAP BRANPAGE for Federal or State office use) Date Date		
1-Yates 1-Mesa 1-Gulf Subsurface Safety Valve: Manu. and Type	17 DESCRIPT PROPOSED OR COMPLETED OPERATIONS (Clearly sta	te all pertinent details, and give pertinent dates.
18. I hereby certify that the foregoing is true and correct SIGNED	 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Drilled to TD of 15700'. Ran 4-1/2" N-80 13. top of liner 14403'. Cemented with 200 sacks per sack. WOC 18 hrs. Drilled out coment to to 1000 PSI for 30 min. Tested OK. Rig relevant. 	te all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* .5 lb/ft. liner set at 15699' s Class H with 5 lbs. gilsonite o 14403'. Pressure tested casing
SIGNED	 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Drilled to TD of 15700'. Ran 4-1/2" N-80 13. top of liner 14403'. Cemented with 200 sacks per sack. WOC 18 hrs. Drilled out coment to 1000 PSI for 30 min. Tested OK. Rig relevantil move in completion unit. O+6-USGS, R 1-Hou 1-Susp 1-W. Stati-Yates 1-Mesa 1-Gulf 	Ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* .5 lb/ft. liner set at 15699' s Class H with 5 lbs. gilsonite o 14403'. Pressure tested casing eased 1-10-82. No further report
APPROVED BY TITLE DATE DATE	 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly staincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Drilled to TD of 15700'. Ran 4-1/2" N-80 13. top of liner 14403'. Cemented with 200 sacks per sack. WOC 18 hrs. Drilled out coment to 1000 PSI for 30 min. Tested OK. Rig relevantil move in completion unit. O+6-USGS, R 1-Hou 1-Susp 1-W. Stal-Yates 1-Mesa 1-Gulf 	Ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* .5 lb/ft. liner set at 15699' s Class H with 5 lbs. gilsonite o 14403'. Pressure tested casing eased 1-10-82. No further report
APPROVED BY TITLE DATE TITLE DATE	 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Drilled to TD of 15700'. Ran 4-1/2" N-80 13. top of liner 14403'. Cemented with 200 sacks per sack. WOC 18 hrs. Drilled out coment to 1000 PSI for 30 min. Tested OK. Rig relevantil move in completion unit. O+6-USGS, R 1-Hou 1-Susp 1-W. Statistical depths and type	Ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* .5 lb/ft. liner set at 15699' s Class H with 5 lbs. gilsonite o 14403'. Pressure tested casing eased 1-10-82. No further report
APPROVED BY DATE DATE	 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Drilled to TD of 15700'. Ran 4-1/2" N-80 13. top of liner 14403'. Cemented with 200 sacks per sack. WOC 18 hrs. Drilled out coment to to 1000 PSI for 30 min. Tested OK. Rig relevant of the second start of the s	Ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* .5 lb/ft. liner set at 15699' s Class H with 5 lbs. gilsonite o 14403'. Pressure tested casing eased 1-10-82. No further report afford, Hou 1-DMF
CONDITIONS OF APPROVAL, JAN'Z 0 1982	 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly staincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine. Drilled to TD of 15700'. Ran 4-1/2" N-80 13. top of liner 14403'. Cemented with 200 sacks per sack. WOC 18 hrs. Drilled out coment to to 1000 PSI for 30 min. Tested OK. Rig relevant in the completion unit. 0+6-USGS, R 1-Hou 1-Susp 1-W. States 1-Yates 1-Mesa 1-Gulf Subsurface Safety Valve: Manu. and Type	Ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* .5 lb/ft. liner set at 15699' s Class H with 5 lbs. gilsonite to 14403'. Pressure tested casing eased 1-10-82. No further report afford, Hou 1-DMF
	 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine. Drilled to TD of 15700'. Ran 4-1/2" N-80 13. top of liner 14403'. Cemented with 200 sacks per sack. WOC 18 hrs. Drilled out coment to to 1000 PSI for 30 min. Tested 0K. Rig relevant to 1000 PSI for 30 min. Tested 0K. Rig relevant in completion unit. 0+6-USGS, R 1-Hou 1-Susp 1-W. State 1-Yates 1-Mesa 1-Gulf Subsurface Safety Valve: Manu. and Type	Ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* .5 1b/ft. liner set at 15699' s Class H with 5 lbs. gilsonite 0 14403'. Pressure tested casing eased 1-10-82. No further report afford, Hou 1-DMF
	 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine Drilled to TD of 15700'. Ran 4-1/2" N-80 13. top of liner 14403'. Cemented with 200 sacks per sack. WOC 18 hrs. Drilled out cament to to 1000 PSI for 30 min. Tested 0K. Rig relevant to 1000 PSI for 30 min. Tested 0K. Rig relevant line of the top of line of li	Ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* .5 1b/ft. liner set at 15699' s Class H with 5 lbs. gilsonite 0 14403'. Pressure tested casing eased 1-10-82. No further report afford, Hou 1-DMF
	 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine. Drilled to TD of 15700'. Ran 4-1/2" N-80 13. top of liner 14403'. Cemented with 200 sacks per sack. WOC 18 hrs. Drilled out cament to to 1000 PSI for 30 min. Tested 0K. Rig relevant to 1000 PSI for 30 min. Tested 0K. Rig relevant in completion unit. 0+6-USGS, R 1-Hou 1-Susp 1-W. State 1-Yates 1-Mesa 1-Gulf Subsurface Safety Valve: Manu. and Type	Ate all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and ent to this work.)* .5 1b/ft. liner set at 15699' s Class H with 5 lbs. gilsonite 0 14403'. Pressure tested casing eased 1-10-82. No further report afford, Hou 1-DMF

· Section of

•

.

•

h 🤃 👬 🐴
