

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Pogo Producing Company ✓
3. ADDRESS OF OPERATOR
P.O. Box 10340 Midland, Texas 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 580' FNL & 2130' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Run & Cement Surface Pipe ☐

☐
☐
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

DEC 8 1980
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/28/80: 220' MW 8.8, Vis 40, Ph 8.5. Ran 6 jts (219.08') 10 3/4" 40.5# K-55 Rge 3 STC csg. Shoe @ 203', HOWCO cem w/ 200 sxs Cl C 2% CaCl, CIP @ 12:45 am CST 11/28/80. Circ 25 sxs. USGS notified but not present. WOC 6½ hrs.
11/29/80: 220' 13½ hrs WOC, cut off csg, NU, test csg w/ 500#, OK. Reduce hole size to 7 7/8" and drl cement plug.
11/30/80: 750' Drlg, Anh., mud wt. 8.8#, Vis 28, Ph 9.0.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Div. Oper. Mgr. DATE December 4, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

