

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Pogo Producing Company ✓

3. ADDRESS OF OPERATOR

P.O. Box 10340 Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 580' FNL & 2130' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

UL-C

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒

LEASE

NM 12559

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Brantley Federal

9. WELL NO.

1

O. C. A.
ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME

Wildcat Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 23, T-26-S, R-23-E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
2954' GE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/11/80: 2640' MW 10.4, Vis 36. Logged w/Schlumberger - HOWCO spotted Plug #1 @ 2540'-2640' w/75 sxs Cl C cement w/0.5% HR-4. Plug #2 @ 1430'-1530' w/50 sxs Cl C cement w/0.5% HR-4.

12/12/80: HOWCO spotted cem Plug #3 @ 170'-270' w/50 sxs Cl C Neat. Plug #4 from surface to 10' w/10 sxs Cl C Neat.

12/13/80: Cut off well head, weld on plate and marker, clean up location, fence mud pits. P & A 12/12/80 as dry hole. FINAL REPORT.

Casing left in hole: 219.08' 10 3/4" 40.5# K-55 Rge 3 STC @ 220'.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

[Signature]

TITLE Div. Oper. Mgr.

DATE December 22, 1980

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Posted ID-2
P+A
1-16-81