




THE FOLLOWING CONSTITUTE MINIMUM BLOWOUT PREVENTER REQUIREMENTS

- ONE DOUBLE GATE BLOWOUT PREVENTER WITH LOWER RAMS BLIND AND UPPER RAMS FOR PIPE, ALL HYDRAULICALLY CONTROLLED, OPENING OR PREVENTERS BETWEEN RAMS.
- OPENING TO BE FLANGED, STUDDED OR CLAMPED AND AT LEAST TWO INCHES DIAMETER.
- ALL CONNECTIONS FROM OPERATING MANIFOLD TO PREVENTERS TO BE ALL STEEL ROSE OR TUBE A MINIMUM OF ONE INCH IN DIAMETER.
- THE AVAILABLE CLOSING PRESSURE SHALL BE AT LEAST 15% IN EXCESS OF THAT REQUIRED WITH SUFFICIENT VOLUME TO OPERATE THE PREVENTERS.
- ALL CONNECTIONS TO AND FROM PREVENTERS TO HAVE A PRESSURE RATING EQUIVALENT TO THAT OF THE B.O.P.'s.
- HANDVAL CONTROLS TO BE INSTALLED BEFORE DRILLING CEMENT PLUG.
- VALVE TO CONTROL FLOW THROUGH DRILL PIPE TO BE LOCATED AT RIG FLOOR.
- CHOKE MAY BE EITHER POSITIVE OR ADJUSTABLE... choke spool may be used between rams.

REPCO II
ONE HYDRAULIC DUAL BLOWOUT PREVENTER