		,- 463	_		
Form 9-331 (May 1963)	UI ED STATES DEPARTMENT OF THE INTERI	SUBMIT IN TR: (Other instruction verse side)	CATE* on re-	Form approv Budget Bure 5. LEASE DESIGNATION	au No. 42-R1424.
/	GEOLOGICAL SURVEY			NM 35607	
(Do not use this for	RY NOTICES AND REPORTS (m for proposals to drill or to deepen or plug to se "APPLICATION FOR PERMIT—" for such p	ack to a different reservoi:	r. ,	6. IF INDIAN, ALLOTTE	E OR TRIBE NAME
OIL GAS X	OTHER			7. UNIT AGREEMENT N	AME
2. NAME OF OPERATOR		S. FARM OR LEASE NAME			
lke Lovelady, I		Ross Draw Federal Com.			
3. ADDRESS OF OPERATOR		9. WELL NO.			
	6; Midland, Texas 79702 ort location clearly and in accordance with any .	State requirements.*		10. FIELD AND POOL, O Wildcat 11. SEC., T., R., M., OR SURVEY OR AME	BLK, AND
660' FNL & 1980	' FWL of Sec.33		ij . i	Sec.33,T-2	6 S, R-30-E
14. PERMIT NO.	16. ELEVATIONS (Show whether DE	, RT, GR, etc.)		12. COUNTY OR PARIS	H 13. STATE
	% 943.5 Gr.			Eddy	New Mexic
16.	Check Appropriate Box To Indicate N	lature of Notice, Repo	ort, or O	ther Data	
NOTICE OF INTENTION TO:				ENT REPORT OF:	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON®	WATER SHUT-OFF FRACTURE TREATME SHOOTING OR ACIDE		REFAIRING ALTERING O	CASING

NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:	•
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other)XSpud & See	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS et 13-3/8" Csq.		WATER SHUT-OFF REPAIRING FRACTURE TREATMENT ALTERING SHOOTING OR ACIDIZING ABANDONM (Other) (Note: Report results of multiple completion Completion or Recompletion Report and Log of Management (Note) (N	CASING

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Set 70' 20" Conductor Csg.


Spudded well on 5/21/81

18

5/4/81 to 6/3/81 drilled 17-1/2" hole to 3290".

6/3/81 Ran 80 Jts 13-3/8" 68# ST&C K-55 8rd Csg. Set @ 3290'.

6/4/81 Cemented W/3515 Sks. Halliburton Lite + 300 Sks Class "C" Neat 2% CaCl. cir. 600 Sks. Cement.



U.S. GE ROSW	EOLOGICAL SURVEY ELL, NEW MEXICO		DLOGICAL SURVEY
	TITLE Mgr. of	Drlg. & Production DATE_	6/15/81
(This space for Federal or State office of APPROVED BY	TITLE	DATE	
	*See Instructions on Rev	erse Side	