

NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

DEC 14 1981

2. NAME OF OPERATOR

Getty Oil Company

O. C. D.

3. ADDRESS OF OPERATOR

P.O. Box 730 Hobbs, NM 88240

ARTESIA, OFFICE

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Unit 1 tr. G, 1880' FNL & 1980' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐
☐

NOV 25 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE

NM-13413

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Salt Draw "11" Fed Com. #1

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 11, T25S, R28E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

2454.4 GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/9/81 Drilled 12 1/4" hole to 9830'. Ran 55 jts. 9 5/8" 47# T-95 8R LT&C and 182 jts. 9 5/8" 40# S-95 8R LT&C casing and set at 9830'.

10/10/81 Howco cemented casing as follows:
First Stage: 760 sxs. Lite; .6% Halad 9, 3# Gilsonite; 1/4# Flocele and tailed in w/300 sxs. class "H" Cement w/.8% Halad 9. Cement did not circulate.

Second Stage: 2100 sxs. Lite, .6% Halad 9, 3# Gilsonite 1/4# Flocele and tailed in w/200 sxs. class "H" cement w.8% Halad 9, and 3# salt. Cement did not circulate. Total cement - First Stage 1060

Second Stage 2300
3360 sxs.

10/11/81 Ran temperature survey and found top of cement @ 1315'.

Subsurface Safety Valve: Manual Type

ROGER A. CHAPMAN

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

DEC 11 1981
Dale R. Crockett

TITLE Area Superintendent

DATE November 23, 1981

(This space for Federal or State office use)

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

TITLE

DATE