## STATE OF NEW MEXICO ENERGY AND MIMERALS DEPARTMENT

wa, at Cartes accrives		
MOLTUBIATED	1	1
SANTA FE	17	T
FILE	17	1
U.3.0.5.		
LAND OFFICE	1	
NO7.58550	1	1

## OIL CONSERVATION DIVISION P. O. BOX 2088

Form C-103 - Revised 10-1-7

SANTA FE, NEW MEXICO 87501	461,360 10-1-
U.S.O.S.	Sa. Indicate Type of Lease
LAND OFFICE	State XX Foo
NOTARSEO	5. State Olf 6 Gas Lease No. L-5367
SUNDRY NOTICES AND REPORTS ON WELLS 100 NOT USE THIS FORM FOR PROPOSALS TO DRILL ON TO DEEPEN OF PLUG BACK TO A DIFFERENT REGENTED 101 "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)	
OIL GAS X OTHER-	7. Unit Agreement Name
2. Name of Operator SEP 1 6-1981	8. Farm or Lease Name
Amoco Production Company	State MA Com
P. O. Boy 68 Hobbs NM 88240 ARTESIA, OFFICE	9. Well No.
P.O. Box 68 Hobbs, NM 88240	1 10. Field and Pool, or Wildcat
UNIT LETTER H . 1980 PEET FROM THE NORTH LINE AND 660 FEET FR	
THE East LINE, SECTION 3 TOWNSHIP 25-S RANGE 28-E NMP	
15. Elevation (Show whether DF, RT, GR, etc.)	
2997.9' GL	12. County Eddy
Check Appropriate Box To Indicate Nature of Notice, Report or C	
	T REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON COMMENCE DRILLING OPHS.	PLUG AND ABANDONMENT
PULL OR ALTER CABING CHANGE PLANS CASING TEST AND CEMENT JOB	٠ جــ
OTHER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including work) SEE RULE 1103.	ig estimated date of starting any proposed
Drilled to a TD of 12260 and Ran 2915' of 7-5/8" 38.05# P-110 Liner. 12260' and top of liner 9345'. Cemented with 745 sx Class H with .75% at 8:10 PM 7-28-81. WOC 19-3/4 hrs. Tagged fill at 7478' and washed d circulation material. Tagged cement at 7848' and drilled to 8685'. Dr to liner at 9345'. Set packer at 9245'. Tagged cement at top of liner 9345'-9495'. Ran cement bond log. Spotted 50 sx Class A with 3/4 of 1 Tailpipe set at 8420 and packer set at 7950'. WOC 6 hr. Spotted 350 s cement 9069-9269'. Reduced hole to 6-1/2" and resumed drilling.	CFR-2. Plug down own to 7848'. Lost illed hard cement at 9345'. Drilled % CFR 2 slurry WT16
	•
	•
0 + 6 NMOCD, A 1-Hou 1-GPM 1-W.Stafford, Hour 1-Susp 1-Union of Ca	lif 1-Superior
18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Metabel Metabel Admin. Analyst	DATE 9-11-81
Wa hand	
SUPERVISOR, DISTRICT II	SEP 1 8 1981 ·
CONDITIONS OF APPROVAL, IF ANY:	•