

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

P.O. Box 2760, Midland, Tx. 79702-2760

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & 1980' FEL, Unit B

AT TOP PROD. INTERVAL: same as above

AT TOTAL DEPTH: same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) spud date, surface csg, 1st intermediate csg & core

SUBSEQUENT REPORT OF:

DEC 14 1981
U.S. GEOLOGICAL SURVEY

5. LEASE

030458

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Poker Lake Unit

8. FARM OR LEASE NAME

Poker Lake Unit

9. WELL NO.

53

10. FIELD OR WILDCAT NAME

Eddy Undesignated (Morrow)

11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA

Sec 9, T25S, R31E

12. COUNTY OR PARISH 13. STATE

Eddy Co.

New Mexico

14. API NO.

NA

15. ELEVATIONS (SHOW OF KDB, AND WD)

GL 3390 KB 3412

NOTE: Report results of multiple completion or zone change on Form 9-330

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
Spud 26" hole @10:30 P.M. CST Nov. 7, 1981. Drilled to 775'. Ran 19 jts 20" 94# H-40 ST&C csg. Set csg @775'. Cemented w/800 sx Lite plus additives. Tailed in w/200 sx Class "C" plus additives. Circ out 143 sx. PD @8:30 P.M. CST Nov. 11, 1981. WOC 28 hrs. NU BOPE & test to 500 psi--okay. Drld. collar, shoe & cement. Drld. 17-1/2" hole to 4271'. Ran 14 jts 68# S-80 ST&C + 25 jts 61# S-80 ST&C + 30 jts 61# K-55 ST&C + 38 jts 54.5# K-55 ST&C + 2 jts 68# S-80 ST&C all 13-3/8" csg. Set csg @4271'. Cemented w/3600 sx Lite + additives & tailed in w/250 sx Class "C" + additives. Circ out 250+ sx. PD @1:45 A.M. CST Nov. 27, 1981. WOC 81 hrs. NU BOPE. Tested BOPE. Did not hold. ND BOPE. NU new BOPE. Could not test BOPE. ND BOPE. NU new BOPE. Test rams to 3000#, Hydril to 2000#, csg to 2000#, Kelly to 3000#, manifold to 3000#. All held okay. Drld. plug & cement. Drld. 12-1/4" hole to 4310' PU core barrel. Cored Delaware Dec. 6, 1981 from 4310-4370' w/7-7/8" bit. Cored 60' & rec. about 56'. Drld out 7-7/8" hole w/12-1/4" bit & drld ahead w/12-1/4" bit.
Subsurface Safety Valve: Manu. and Type Set @ Ft.

18. I hereby certify that the foregoing is true and correct

(JDR)

SIGNED

R. P. Murphy, Jr.

TITLE

Gen. Prod. Mgr.

DATE 12/11/81

ACCEPTED FOR RECORD
ROGER A. CHAPMAN
APPROVED BY
CONDITIONS OF APPROVAL, IF ANY

DEC 15 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

(This space for Federal or State office use)

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.