

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

RECEIVED BY
MAY 08 1986
O. C. D.

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Wood & Locker, Inc. ✓		5. State Oil & Gas Lease No. L-6292
3. Address of Operator 505 N. Big Spring, Suite 600, Midland, Texas 79701-8602		7. Unit Agreement Name ---
4. Location of Well UNIT LETTER G, 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 23 TOWNSHIP 25-S RANGE 27-E NMPM.		8. Farm or Lease Name Moore State
15. Elevation (Show whether DF, RT, GR, etc.) 3052' RKB, 3040' GR		9. Well No. 1
		10. Field and Pool, or Wildcat Wildcat - Bone Springs
		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Set CIBP @ 5807' RKB inside 4-1/2", 11.60# casing & cap with 100' of cement.
- Cut & pull 4-1/2" casing from 3900' RKB.
- Spot 35 sacks Class "C" with 2% calcium chloride from 4030' to 3797' RKB. WOC 2 hrs. Tag top of cement.
- Spot 35 sacks Class "C" with 2% calcium chloride from 2275' to 2139' RKB. WOC 2 hrs. Tag top of cement.
- Spot 35 sacks Class "C" from 460' to 325' RKB.
- Spot 10 sacks Class "C" from 54' RKB to 3' BGL.
- Weld 1/2" steel plate on 13-3/8" casing & install dry hole marker.

NOTE: Well to be loaded with 10 ppg salt gel mud between plugs. See attached wellbore schematic.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED D. M. Johnson D. M. Johnson

TITLE President

DATE 5-7-86

Original Signed By
Mike Williams

Oil & Gas Inspector

APPROVED BY _____

TITLE _____

DATE MAY 12 1986

CONDITIONS OF APPROVAL, IF ANY:

Placed in sufficient time to witness

WOOD & LOCKER, INC.

Prepared by:	Initial	Date
Approved by:		5/2/86

State Lease L-6292

LEASE Moore State

WELL NO. 1

FIELD

