

C/SF

Form 9-331
Dec. 1973

RECEIVED

Form Approved
Budget Bureau No. 42-R1424 RECEIVED BY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

JAN 13 1986

G. C. D.
ARTESIA, OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐ DRY HOLE

2. NAME OF OPERATOR
Sundance Oil Company

3. ADDRESS OF OPERATOR
1675 Larimer St., #800, Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2180' FNL, 1780' FEL
AT TOP PROD. INTERVAL: As above.
AT TOTAL DEPTH: As above.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☒

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

II pulling unit 1-24-84. Bled off 7-5/8" & 10-3/4" casing. Pumped 40 bbls. 10# brine water down tubing to kill well. Installed & tested BOP's. Set CIBP at 11,240'. Spotted 20 sx cement plug from 11,240-11,020'. Spotted 25 sx cement plug from 8700-8518'. Shot off casing at 2100' - recovered 42 jt. 7-5/8" casing. Spotted 25 sx plug from 1846-1601'. Tagged plug at 1680' - spotted 25 sx plug from 1680-1634'. Spotted 25 sx plug from 100' to surface. Cut off wellhead & installed dry hole marker. Job complete 7 a.m. 2/1/84. Well P&A. Location to be cleaned, leveled & reseeded as per BLM stipulations.

* 25sx plug 5142'-5002'.

Unable to pull casing from 2100'. Cut and pulled casing from 1800'. Info from Armond Sandon.
P.W.C. 3/7/84

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED X TITLE Prod. Assistant DATE 2/24/84

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

1-8-84

Post FD-2
3-9-84
P&A