

UNITED STATES Artesia, NM 88210

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐ Storage

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
1800 Wilco Building, Midland, TX 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 412' FWL & 2090 FNL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) Run casing and Perforate ☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to 7100', ran 7" 23#, N-80 casing set at 7099.48'. Cemented with 405 sxs. Class "H" cement. Job complete at 2:30 a.m. 11-29-81. W.O.C. 25 1/2 hrs. and tested casing 3000#, test OK. Top of cement @ 5750'. R.U. McCullough and perforated 7005-7008, 6969-6977, 6899-6910, 6834-6855, 4 spf, .34" holes (172 holes). TIH w/ 2 7/8", 6.5# J-55 EUE ABC tubing. and set at 6912.97. Released rig and shut in for test.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED *John A. Duck* Supervisor Production
ACCEPTED FOR RECORD TITLE Services DATE 12-8-81

ROGER A. CHAPMAN (This space for Federal or State office use)

APPROVED BY *65C 1 1 1981*
CONDITIONS OF APPROVAL

TITLE DATE

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side