

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	RECEIVED BY MAY 12 1986 O. C. D. ARTESIA, OFFICE	5. LEASE DESIGNATION AND SERIAL NO. NM 0557561
2. NAME OF OPERATOR Marline Petroleum Corp. ✓		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 4900 Capitol Bank Plaza, Houston, TX 77002		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FSL & 1980' FWL, K., Sec. 9, T26S, R27E		8. FARM OR LEASE NAME HAY B FEDERAL
		9. WELL NO. 1
		10. FIELD AND POOL, OR WILDCAT Welch-Bone Spring
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 9-26S-27E
12. PERMIT NO. 30-01S-23935	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3274.3 GR	12. COUNTY OR PARISH Eddy
		13. STATE N.M.

### Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

#### NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
(Other) ☐

PULL OR ALTER CASING ☐  
MULTIPLE COMPLETION ☐  
ABANDON\* ☐  
CHANGE PLANS ☐

#### SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☐  
SHOOTING OR ACIDIZING ☐  
(Other) ☐

REPAIRING WELL ☐  
ALTERING CASING ☐  
ABANDONMENT\* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. 8-7-85 Set CIBP @ 5350' & capped with 35' cement.
2. 8-8-85 TIH w/tbg to 5315' & displaced with 9.5#/gal mud-laden fluid.
3. 8-8-85 Set 14.8#/gal cement plugs as follows:
  - a. 25 sx @ 4850' to 4750'
  - b. 25 sx @ 4150' to 4050'
  - c. 25 sx @ 2700' to 2600'
  - d. 25 sx @ 2450' to 2350'
4. 8-8-85 Cut 5½" casing @ 1754', pulled & LD csg.
5. 8-8-85 Set 60 sk 14.8#/gal cement plug @ 1804'.
6. 8-9-85 TIH w/tubing and tagged top cement @ 1680'.
7. 8-9-85 Set 14.8#/gal cement plugs as follows:
  - a. 50 sx @ 1200' to 1100'
  - b. 50 sx @ 370' to 270'
  - c. 50 sx @ 20' to surface
8. 8-9-85 Installed dry hole marker.
9. 8-29-85 Cleared trash from and levelled location.

I hereby certify that the foregoing is true and correct

SIGNED John Ronald

TITLE Consultant

DATE 8-30-85

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE 5-8-86

\*See Instructions on Reverse Side