

30-015-23959

7-28-82

DL/GR

2254-7013'

CD/CN

Surf-7011'

GR/N

2300-6897'

- (1) Set CIBPC 5940 w/100' cap ✓
- (2) 25 SX @ 4500 ✓
- (3) 35 SX @ 2350 + test
- (4) Tie into 4 1/2" annulus + try to pump into shoe cut + pull 4 1/2" @ 2250
- (5) Run 1" down 4 1/2" x 8 5/8" annulus to 350' + Circ cmt
- (6) Spot 35 SX @ 350 inside 4 1/2"
- (7) ^{105X} surface plug mud between all plugs

Shield
No. 153C
HASTINGS, MN
LOS ANGELES-CHICAGO-LOGAN, OH
MCREGOR, TX-LOCUST GROVE, GA
U.S.A.

Southland St #1

2000W 60E - 1-25-27

14" @ 40' Circ	Feb/82
85/8 - 2259 - Circ	(Down Annulus stop wtr flow)
4 1/2 7062 - TOC 4425	(2240 - 3200)
PBTD 6910	Cmt Plug
eff TD 6866	5/5 SX
TD 7002	Junk
DV 7002 @ 4015'	Before comp
BS Perfs 6442 - 6566	BS 5890
6185 - 6338	Del 2116
6026 - 6113	BX 2060
	TX 816

- Proposed
- (1) CIBP 5890 w/cap
 - (2) 10 SX @ 2183-2334
 - (3) 10 SX @ 166-3'

Del- 2392
Bone Spr. - 5893