NH OLD COM. Draund DL Antesia, NM 88210

Artesia, MM oc	) L L V		Form	Approved.		
orm 9-331 Dec. 1973	/				No. 42-R1424	
UNITED STATES	5.	LEASE	7			
C DEPARTMENT OF THE INTERIOR		NM 3560		00.000	F 31 4 5 4 F	-
GEOLOGICAL SURVEY	6.	IF INDIAN, A	ALLOTTEE	UR I RIB	E NAME	
SUNDRY NOTICES AND REPORTS ON WEELS	7.	UNIT AGRE	EMENT N	AME		-
SUNDRY NUTICES AND REPORTS ON WELLS						_
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.) MAY 1-8-1982	8.	FARM OR LI			् हूँ हु	
1. oil gas gas		UCBH WW	Federa	à l		-
<u> </u>	- 9.	WELL NO. 1				
2. NAME OF OPERATOR ARTESIA, OFFICE J. C. Williamson	10.	FIELD OR W	H.DCAT N			-
3. ADDRESS OF OPERATOR	-	Bruchy	Draw D	Taware	5	
890 Midland National Center, Midland, TX 797	0111.	SEC., T., R.	, M., OR E	BLK. AND	SURVEY O	R
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17		AREA Se	26-S, 1			
below.) AT SURFACE: 660' FSL & 660' FWL	12	COUNTY OF			ATE	-
AT TOP PROD. INTERVAL: 660' FSL & 660' FWL		Eddy			w Mexico	)
AT TOTAL DEPTH: 660' FSL & 660' FWL	14.	API NO.				
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,						
REPORT, OR OTHER DATA	15.	ELEVATION 2887.5	IS (SHOW GR	DF, KD	B, AND WE	))
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	L	2007.0	· · · · · · · · · · · · · · · · · · ·	· · · ·		-
TEST WATER SHUT OFF						
RACTURE TREAT			• 5.		가 입수 <sub>11</sub>	
	- (N	OTE: Report r	esults of m	ultiple com	pletion or zor	ne
PULL OR ALTER CASING		change	on Form 9-	-330.) -		
MULTIPLE COMPLETE					ີ	
ABANDON*						
(other) Run & Set Casing X			いがです。 マジン	- E. -	zi. Politika	
<ol> <li>DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine</li> </ol>	te all direction ant to t	pertinent de onally drilled his work.)*	tails, and I, give sul	l give per osurface l	tinent date locations ar	s, nd
5/6/82 - 12 3/4" surface casing set @ 358' w	vith	720 sack	s of C	lass "	Ċ",	
	٠			การกา		
with 2 to 4% CaCl 2%, 1/4# Flocele/sx of cen	nent.		1		35555	
a state of the second by Managalant		t	$\sim 10^{-1}$			15
Cement circulated, witnessed by Minerals Mar	nagen	ient.	e S	图 《图》	10	
					- 198	2
			$1 \leq q$	1 o . 24	8 6 L	- :
				л — 1. С		
Subsurface Safety Valve: Manu. and Type			Set	: @		Ft.
18. I hereby certify that the foregoing is true and correct			÷		· •	
rise Thereby certify that the kneeding is the and conect	tarv	i	5/10/82	)		
SIGNED James To aucon TITLE FIOU. SECTE	cury	DATE				
(This space for Federal or State o	ffice us	e)				
APPROVED BY TITLE		DATE				
CONDITIONS OF APPROVAL, IF ANY				-		
			:			
					$+$ $\pm$	

\*See Instructions on Reverse Side