

UNITED STATES **Artesia, NM 88210**

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Co./
3. ADDRESS OF OPERATOR
1800 Wilco Bldg.; Midland, Texas 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FSL & 660 FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐

(other) Spud & Drlg Operations



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17 1/2" hole on 1/24/82 at 10 AM, Warton Rig #6. Drilled to 346' and ran 13 3/8", 48#, H-40 casing set at 346'. Cemented with 375 sx Class "C" cement and circulated 100 sx to surface. WOC 28 1/2 hrs and tested casing 800 psi, test OK. Reduced hole to 12 1/4" and drilled to 3,614' and ran 9 5/8", 36#, K-55 casing set @ 3,614'. Cemented with 1900 sx Howco Lite cement. RU 1" tubing and cement with 300 sx cement and circ. 5 sx to surface. WOC 30 3/4 hrs and tested casing 1200 psi, test OK. Reduced hole to 8 3/4" and drilled to 11,700' and ran 7", 26#, N-80 casing set @ 11,700'. Cemented with 2975 sx Class "H" cement. Job complete 3 PM, 3-6-82. Top of cement at 4,080'. WOC 82 3/4 hrs and tested casing 2000 psi, test OK. Reduced hole to 6 1/8" and resumed drilling operations.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John D. Deek TITLE Supv. Prod. Svc. DATE 3/12/82

APPROVED BY ROGER A. CHAPMAN

CONDITIONS OF APPROVAL, IF ANY:

MAR 19 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

5. LEASE

USA NM 153111

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

APR 2 1982

8. FARM OR LEASE NAME

El Paso Federal ~~23~~

O. C. D.

ARTESIA, OFFICE

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

~~Ross Draw Area~~ Und. Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

23 - 26 - 30

Ut-M Sec 34, T-25-S, R-24-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

NA

15. ELEVATIONS (SHOW DF, KDB, AND WD)

GL 3042.0