

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COMMISSION
DRAWING NO. 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back or to change a well to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other Storage ☐ JUL 2 1982
2. NAME OF OPERATOR
El Paso Natural Gas Co. ✓ O.C.D.
3. ADDRESS OF OPERATOR
ARVESTA, OFFICE
1800 Wilco Bldg.; Midland, Texas 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 950' FNL & 950' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) Spud & Drlg. Operations

5. LEASE
NM 22207
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Washington Ranch Storage Project
9. WELL NO.
WI Federal #22
10. FIELD OR WILDCAT NAME
Washington Ranch
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 34, T-25-S, R-24-E
12. COUNTY OR PARISH
Eddy
13. STATE
NM
14. API NO.
NA
15. ELEVATIONS (SHOW DF, KDB, AND WD)
GR 3718

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 5-2-82 spudded 12 1/4" hole @ 7 PM, Young Drlg Rig No. 5. Drilled to 820' and ran 9 5/8", 32.3#, H-40 casing set @ 796'. Cemented with 500 sx Class "C" cement. Cemented backside with 600 sx Class "C" cement and followed by 6 yds of Redi-Mix to surface. WOC 21 hrs and tested casing to 800 psi, test OK. Top of cement at surface. Reduced hole to 8 3/4" and drilled to 7000' and ran 7", 23#, N-80 casing set @ 6972.52'. Cemented with 500 sx Class "H" cement and plug down at 1 AM, 5-28-82. Top of cement at 3510'. Released rig @ 8 PM, 5-28-82. Waiting on completion.

Project approved by NMOCD Order No. R-6175-A
Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

John P. Deek

TITLE Supv. Prod. Svc. DATE June 3, 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUL 1 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side