

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐ **10-2-1982**
2. NAME OF OPERATOR **OIL & GAS MINERALS MGMT. SERVICE**
Perry R. Bass
3. ADDRESS OF OPERATOR **ROSWELL, NEW MEXICO**
P. O. Box 2760 Midland, Texas 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL 1980' FWL Unit Letter C
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

7-5/8" Liner

- LC 061672-B
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME **RECEIVED**
Poker Lake Unit
8. FARM OR LEASE NAME **OCT 25 1982**
Poker Lake Unit
9. WELL NO. **O. C. D.**
52
10. FIELD OR WILDCAT NAME **ARTESIA, OFFICE**
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 33, T25S, R31E
12. COUNTY OR PARISH **Eddy**
13. STATE **New Mexico**
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3302.3' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 8-1/2" hole to 14,727'. Logging 10-14-82.

Ran 66 jts. 7-5/8" P-110 39# FL45 threads with MWL Hanger. Hung liner 2' off bottom @ 14,725'. Top of liner @ 12,196'.

Cemented with 800 sx Class "H" cement with additives. Plug down @ 2:15 a.m. CDT 10-18-82. WOC & LD DP 20-3/4 hrs. Drilling hard cement in 9-5/8" csg. 10-19-82.

Subsurface Safety Valve: Manu. and Type

N/A

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. C. Houtchens TITLE Sr. Prod. Clerk DATE 10-20-82

ACCEPTED FOR RECORD (ORIG. SGD.) DAVID R. GLASS
APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL IF ANY:

OCT 21 1982

**U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO**

See Instructions on Reverse Side