

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Artasia, NM

SECTION

Form Approved.
Budget Bureau No. 42-R1474

455

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR

THE SUPERIOR OIL COMPANY

3. ADDRESS OF OPERATOR

P.O. BOX 3901 MIDLAND, TEXAS 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 660' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☒

☐

88210ASE
NM-28172

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
DELTA FEDERAL

9. WELL NO.

2

10. FIELD OR WILDCAT NAME
WILDCAT (MORROW)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 7, T24S, R26E

12. COUNTY OR PARISH

EDDY

13. STATE

NEW MEXICO

14. API NO.

38-315-24187

15. ELEVATIONS (SHOW DF, KDB, AND WD)

GR: 3413.8

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-19-82 Cementing Plug #1 w/DP @ 11,200' w/45 sks Class H cmt + add. WOC.
Plug #2 w/DP @ 9200' w/45 sks Class H + add. Drop down to 9200'
to check plug - no plug. Plug #3 w/DP @ 9200' w/45 sks Class H +
add. WOC for plug #3. Circ out plug #2 while WOC on plug #3.
10-20-82 Circ & WOC for plug #3 @ 8960'. Plug #4 w/DP @ 4300' w/25 sks
Class H; 100' plug, TOC @ 4200'.
11-1-82 Pulled 3917' 7 5/8" Casing.
11-3-82 Plug #5 @ 3967' w/40 sks Class C, TOC @ 3872'.
11-4-82 Plug #6 @ 1726' w/60 sks Class C, TOC @ 1621'.
11-5-82 Plug #7 @ surface w/15 sks Class C.

Post FD-2
11-25-83
P + A

FINAL REPORT

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G.E. TATE TITLE AREA PROD. SUPT. DATE 1-27-83

(This space for Federal or State office use)

APPROVED BY Charles S. Dahlen TITLE
CONDITIONS OF APPROVAL, IF ANY

DATE 12-18-82 **RECEIVED**

JAN 1 1983

*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY
NEW MEXICO