FLOW & MONITOR — 4 POINT

Page 1 Data by

Field Data Sheet

☐ Initial ☐ Annual ☐ Special

10/10/82

Company: PERRY R. BASS

Farm or Lease Name: POKER LAKE UNIT Well No. 58

Unit: Sec. 27 Twp-Blk. 24 S Rge-Sur. 31 E

County or Parish: EDDY State: NEW MEXICO

Field: Reservoir: WOLFCAMP Location: 1980 FSL 1980 FWL

Prover: Meter Run: 4.026 Taps: FLG. Connection: AIR

Completion Date: 10-8-82 Total Depth: 12,700' Plug Back T.D.: 12,566' Elevation: 3493 GL

Csg. Size: 9 5/8" Wt. 53# d Set at Perforations: From 3519 KB

Tbg. Size: 2 3/8 Wt. d Set at Perforations: From 12700 To

Type Completion (Describe): SINGLE GAS WELL Packer Set at

Producing Thru: TBG. Reservoir Temp. F Mean Ground Temp. F: 60 Barom. Press. Pa: 13.2

L H Gg. %CO_2 %N_2 H_2S

1.5 BBLS PER I

Time of Reading	Elap. Time Hrs	Wellhead Working Press. Tbg. Psig	Csg. Psig	Temp. F	Press. Psig	Diff	Temp. F	Orifice	Vol. Mcf/d	Choke Size	Tank Gauge Top	H_2O	BBLS in Tank Top	H_2O	Oil	BBLS Prod H_2O	Oil
0715		3750	900		500	6.0	60	.750	195	4/64	9"	0	15	0	15	0	0
0745	30min	3800	"		500	6.0	88	.750	195	"							
0815	1	3885	"		580	8.0	120	"	240	"	10"	0	16.0	0	16.5	0	1.5
0915	2	3820	"		470	10.0	120	"	240	5/64	11"	0	18.0	0	18.0	0	3.0
1015	3	3820	"		500	11.0	112	"	270	"	14"	0	21.0	0	21.0	0	6.0
1115	4	3860	"		450	10.0	106	"	235	"	16"	1"	24.0	1.5	22.5	1.5	7.5
1215	5	3920	"		470	5.0	100	"	195	"	19"	1"	28.5	1.5	27.0	1.5	12.0
1315	6	4000	"		510	6.0	96	.750	197	"	21"	1"	31.5	1.5	30.0	1.5	15.0
1415	7	4000	"		530	6.0	94	"	200	"	24"	1"	34.5	1.5	33.0	1.5	18.0
1515	8	4000	"		530	7.0	90	"	220	"	4[illegible]"	1"	37.5	1.5	36.0	1.5	21.0
1615	9	4000	900		530	6.0	88	"	[illegible]	5/64	[illegible]	[illegible]	[illegible]	1.5	39.0	1.5	24.0
1715	10	4000	"		530	7.0	88	"	220	"	30"	[illegible]	[illegible]	1.5	42.0	1.5	27.0
1815	11	4000	"		530	6.0	87	"	200	"	33"	[illegible]	[illegible]	[illegible]	[illegible]	1.5	30.0
1915	12	4000	"		490	8.0	88	.750	220	"	35"	[illegible]	[illegible]	[illegible]	[illegible]	1.5	33.0
2015	13	4000	"		530	7.0	88	"	220	"	35"	1"	52.5	1.5	51.0	1.5	36.0
2115	14	4000	"		540	6.5	86	"	210	"	37"	1"	55.5	1.5	54.0	1.5	39.0
2215	15	4000	"		530	7.0	87	"	220	"	38"	1"	58.5	1.5	57.0	1.5	42.0
2315	16	4000	"		510	8.0	87	"	230	"	41"	1"	61.5	1.5	60.0	1.5	45.0
0015	17	4000	"		480	8.0	89	"	220	5/64	43"	1"	64.5	1.5	63.0	1.5	48.0
0115	18	4000	"		480	7.0	90	"	220	"	45"	1"	67.5	1.5	66.0	1.5	51.0
0215	19	4000	"		530	8.0	90	"	220	"	47"	1"	70.5	1.5	69.0	1.5	54.0
0315	20	4000	900		510	6.0	88	"	197	"	49"	1"	73.5	1.5	72.0	1.5	57.0
0415	21	4020	"		480	8.0	86	"	220	"	51"	1"	76.5	1.5	75.0	1.5	60.0
0515	22	4020	"		520	5.0	84	"	185	"	52½"	1"	78.5	1.5	77.25	1.5	62.25
0615	23	4025	"		520	8.0	90	"	230	"	54½"	1"	81.75	1.5	80.25	1.5	65.25
0715	24	4025	900		510	8.0	88	.750	227	5/64	56"	1"	84.0	1.5	82.5	1.5	67.50

BBLS PER HR.

H_2O	Oil
0	1.5
0	1.5
0	3.0
0	3.0
0	4.5
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	3.0
0	2.25
0	3.0
0	2.25