

Drawer 1D
Artesia, NM 88210

45F
For approval.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR
Perry R. Bass

3. ADDRESS OF OPERATOR
P. O. Box 2760 Midland, Texas

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL, 660' FEL, Unit Letter A
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

DST #1 & P & A

(X)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly and in briefest details, and give pertinent dates, including estimated date of starting any proposed work. If well is being plugged, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to the well.)

Drilled 6-1/4" hole to 5375' 11-10-82.

DST #1 5236'-5200' (36') Delaware.

Open 66 min. Very weak blow. SI 180 min. IHP 2424 psi, FP 34 psi - 309 psi, SIP 2396 psi, FHP 2435 psi.

Recovered 546' = 2.1 bbls SW with skim of oil on top

CI 65,000 Top

CI 104,000 Middle

CI 125,000 Bottom .04 @ 62°F

Pit mud 0.1 @ 60°F 41,000 CI

Sampler 200 psi, no gas, no oil. 2300cc SW .03 @ 60°F.

Drilled 6-1/4" hole to 6250'. Log & prep. to P & A.

RIH with jet cutter & cut csg. @ 2500' RD Geosource & pull csg. out of hole.

Recovered 2500' 7" 23# K-55 LT&C csg.

Subsurface Safety Valve: Manu. and Type

N/A

Set @

(over)
Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

R.C. Hartman

TITLE

Sr. Prod. Clerk

DATE

NOVEMBER 17, 1982

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY
CONDITIONS OF

APPROVAL OF ANY

NOV 19 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side

5. LEASE

NM 02860

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Poker Lake Unit

8. FARM OR LEASE NAME

Poker Lake Unit

9. WELL NO.

55

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 19, T24S, R30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3182' GL

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. Consult local

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between, and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

Run in hole & set #1 plug @ 3400'-3500' cement with 40 sx Class "C" neat with additives.

Set plug #2 @ 2450'-2550' with 45 sx Class "C" neat with additives.

Set plug #3 @ 450'-550' with 45 sx Class "C" neat with additives and 10 sx @ surface.

Released rig @ 9:00 p.m. 11-14-82.

Well plugged and abandoned. Final Report.