

UNITED STATES OIL CONS. COMMISSION  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug well to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ **OCT 15 1982**
2. NAME OF OPERATOR  
J. C. Williamson **O. C. D.**
3. ADDRESS OF OPERATOR  
P. O. Box 16 Midland, Texas 79702 **ARTESIA, OFFICE**
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL & 660' FEL  
AT TOP PROD. INTERVAL: 660' FNL & 660' FEL  
AT TOTAL DEPTH: 660' FNL & 660' FEL

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Run & Set Casing	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

5. LEASE  
NM 20367
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
MWJ Federal
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Section 35, T-26-S, R-29-E
12. COUNTY OR PARISH  
Eddy
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
2882.2 GR

(NOTE: Report results of multiple completion or zone change on Form 9-130)

OIL & GAS  
MINERALS MGMT. SERVICE  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/7/82 - Ran 148 joints of 4 1/2", 10.5#, J, ST & C, Range 3 casing (6229.39'), DV tool @ 4456', casing @ 6220'. Cemented by Halliburton with/ 1st- 600 sacks of 50/50 POZ "C", 6# salt and 1/4# flocele/sx, Plug Down at 10:30 PM. Circulated 60 sacks off top of DV tool. 2nd - 100 sacks of Halliburton light, 10# salt and 1/3# flocele/sx and 650 sacks of 50/50 POZ, 6# salt and 1/4# flocele/sx. PD at 5:30 AM on 10/8/82. Did not circulate.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED James L. Crawford TITLE Prod. Secretary DATE 10/12/82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL IF ANY:

**OCT 14 1982**

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side