

OIL CONSERVATION DIVISION

P. O. BOX 2048

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	☒
LAND OFFICE	☒
OPERATOR	☒

JAN 07 1983

O.C.D.

ARTESIA, OFFICE

5a. Indicate Type of Lease
State ☒ For ☐

5. State Oil & Gas Lease No.

LG 690

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER N 660 FEET FROM THE North LINE AND 1980 FEET FROMTHE West LINE, SECTION 2 TOWNSHIP 26S RANGE 31E NMPM.

7. Unit Agreement Name

Almost Texas Unit

8. Farm or Lease Name

Almost Texas Unit

9. Well No.

1

10. Field and Pool, or Wildcat
Wildcat Morrow

11. Elevation (Show whether DF, RT, GR, etc.)

3244' GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐PLUG AND ABANDON ☐
CHANGE PLANS ☐OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPERATIONS ☐
CASING TEST AND CEMENT JOBS ☒ALTERING CASING ☐
PLUG AND ABANDONMENT ☐OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103.

TD 140'. Moved in rotary rig 12-23-82. Ran 70' of 20" conductor pipe. Reamed hole to 70' to 17-1/2". Ran 19 joints of 13-3/8" 54.5# J-55 casing set at 751'. 1-Texas Pattern notched guide shoe set at 751'. Insert float set at 711'. Cemented w/400 sacks Class "C" 2% CaCl₂, 1/4#/sacks celloseal. Tailed in w/400 sacks Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 2:00 AM 1-3-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 7:00 AM 1-6-83. WOC 77 hrs. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED BY Larry L. BrooksTITLE Production SupervisorDATE 1-7-83

Larry L. Brooks

Geologist

APPROVED BY

TITLE

DATE 1/10/83CONDITIONS OF APPROVAL NMOC DIST. II