

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Rustler 856	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Anhy	T. Strawn 14059	T. Kirtland-Fruitland	T. Penn. "C"
T. Salt	T. Atoka 14154	T. Pictured Cliffs	T. Penn. "D"
D. Salt 3970	T. Miss	T. Cliff House	T. Leadville
T. Lamar Lime 4187	T. Devonian	T. Menefee	T. Madison
T. Bell Canyon 4226	T. Silurian	T. Point Lookout	T. Elbert
T. Bell Canyon 4226	T. Montoya	T. Mancos	T. McCracken
T. Bone Springs 8207	T. Simpson	T. Gallup	T. Ignacio Quartz
T. Bone Springs 8207	T. McKee	T. Base Greenhorn	T. Granite
3rd B. Springs 11017	T. Ellenburger	T. Dakota	
T. Grayburg	T. Gr. Wash	T. Morrison	
T. San Andres	T. Granite	T. Todilto	
T. Glorieta	T. Delaware Sand	T. Entrada	
T. Paddock	T. Bone Springs	T. Wingate	
T. Blinnsbry	T. Morrow Lime 14592	T. Chinle	
T. Tubb	T. Morrow Clas. 15124	T. Permian	
T. Drinkard	T. Lwr Morrow 15666	T. Penn. "A"	
T. Abo			
T. Wolfcamp 11480			
T. Penn.			
T. Cisco (Beugh C)			

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.	
No. 2, from.....to.....feet.	
No. 3, from.....to.....feet.	
No. 4, from.....to.....feet.	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	406	406	Surface, Gravel, Redbeds	9562	9884	322	Lime, Shale
406	2764	2358	Anhydrite, Redbeds	9884	10700	816	Sand, Lime, Shale
2764	3700	936	Anhydrite, Salt	10700	11180	480	Shale, Lime
3700	3766	66	Lime, Sand, Salt	11180	11660	480	Sand, Lime, Shale
3766	4030	264	Salt	11660	12230	570	Lime, Shale
4030	4720	690	Anhy, Lime, Salt, Shale	12230	12440	210	Shale
4720	5052	332	Sand	12440	12590	150	Shale, Lime, Tr. Chert
5052	5500	448	Shale, Sand	12590	12840	250	Shale, Lime
5500	5820	320	Sand	12840	12900	60	Shale, Lime, Chert
5820	6076	256	Sand, Shale	12900	13440	540	Shale, Lime, Tr. Sand
6076	6430	354	Sand	13440	13990	550	Shale
6430	8060	1630	Sand, Shale	13990	14580	590	Shale, Lime, Sand, Tr. Chert
8060	8162	102	Sand, Shale, Lime	14580	14680	100	Lime
8162	9178	1016	Shale, Lime	14680	15320	640	Lime, Shale, Chert, Sand
9178	9562	384	Sand, Shale, Lime	15320	15750	430	Sand, Shale
				15750	15900	150	Shale