

YATES PETROLEUM CORPORATION  
Almost Texas Unit #1  
Section 2-T26S-R31E  
Eddy County, New Mexico

#27: ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.:

DEPTH INTERVAL

TREATMENT

8150'	Pumped 100 bbls brine water, 10 bbls WMW-1, 10 bbls fresh water spacer, 10 bbls surebond, 10 bbls fresh water spacer, 1000 sacks Super C, .4% CF-2, .3% CF-14, 3.42#/sack salt and 200 sacks "H" and .5% CF-14.
7100'	Pumped 10 bbls WMW-1, 5 bbls spacer, 10 bbls surebond, 10 bbls spacer and 1000 sacks Super C and 100 sacks "H" and 5/10% CF-14.
8023-8035'	Acidized with 1500 gallons 7-1/2% NEFE acid and ball sealers.  Squeezed with 100 sacks Class H, 4/10% fluid loss and 50 sacks "H" Neat. Squeezed to 1800 psi with 139 sacks in formation.
7423-7442'	Acidized with 1500 gallons 7-1/2% HCL acid and ball sealers. Frac'd (via 2-7/8" tubing) with 21500 gallons 30# crosslink gel and 75000# 16-30 Ottawa sand.