

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYNM DIST. CONS. COMMISSION
Dra. DD
Artesia, NM.
SUBMIT IN TRIPPLICATE
(Other instructions on re-
verse side)88210 Form approved.
Budget Bureau No. 42-R1124.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. NAME OF OPERATOR Gulf Oil Corporation	3. ADDRESS OF OPERATOR P. O. Box 670, Hobbs, NM 88240	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 990' FNL & 660' FEL	5. LEASE DESIGNATION AND SERIAL NO. NM 11038	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	7. UNIT AGREEMENT NAME	8. FARM OR LEASE NAME Booth "BP" Federal	9. WELL NO. 1	10. FIELD AND POOL, OR WILDCAT Brushy Draw Delaware	11. SEC. T. R. M. OR ALK. AND SURVEY OR AREA Sec 23-T26S-R29E	12. COUNTY OR PARISH Eddy	13. STATE NM
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 2957' GL											

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZINGREPAIRING WELL
ALTERING CASING
ABANDONMENT*(Other) Recomplete Delaware(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Tag sand 3396'. Tried to circulate sand off RBP, would not circulate. Load hole with fresh water and circulate sand off RBP; release RBP and POH. Swabbed, water only. Move RBP to 3345', swab water only. POH with RBP. Set CIBP at 3290', test 1000# 15 min-ok. Tag CIBP at 3205'. Knock CIBP to 3500'. Set CIBP at 3290', test 1500#. Spot 10% acetic acid 3246'-3100'. Perf. 3111-15', 3160-64', 3231-35' with (2) 1/2" JHPF. GIH with SN, tubing and rods. Will P&A well.

OIL & GAS
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED R. D. Pite TITLE Area Engineer DATE 6-6-83(This space for Federal use only)
(ORIG. SGD.) DAVID R. GLASSAPPROVED BY DAVID R. GLASS TITLE Area Engineer DATE 6-6-83

CONDITIONS OF APPROVAL IF ANY:

ROSWELL, NEW MEXICO *See Instructions on Reverse Side