

C/87

Form 9-331
Dec. 1973

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

RECEIVED

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR

Cities Service Company

3. ADDRESS OF OPERATOR

P.O. Box 1919 - Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1780' FSL and 1980' FEL

AT TOP PROD. INTERVAL: Same as above

AT TOTAL DEPTH: Same as above

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

☐
☐
☐
☐
☐
☐
☐
☐

(other) Spud, Run, and Set Surface Csg.

5. LEASE

NM 38632

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal X Com.

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Undesignated Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 8 - T26S - R27E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

NA

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3201' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 400' Red Beds. Prep. to drill ahead. MIRU and spudded a 20" hole @ 1200 MST 12-26-82. Drilled to a TD of 408' in Red Beds. Ran and set 9 jts. (353') of 16" 65# H-40 casing at 379'. Cemented with 475 sacks Class C cement plus 2% CaCl₂ and 1/4# Flocule. PD @ 1515 MST 12-28-82. Cement circ. WOC 18 hours. Tested casing to 800# for 30 mins. - OK.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Edmar S. Stast Region Operations
TITLE Manager-Production DATE 12/20/82

ACCEPTED FOR RECORD

(ORIG. SGD.) DAVID R. GLASS

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL

JAN 13 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

Instructions on Reverse Side

RECEIVED

JAN 11 1983

OIL & GAS
MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.