

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐ **JAN 18 1983**
2. NAME OF OPERATOR
Cities Service Company **O.C.D.**
3. ADDRESS OF OPERATOR
P.O. Box 1919 - Midland, Texas **ARTESIA OFFICE 79702**
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1780' FSL & 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same as above
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
NM 38632
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal X
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
~~Undesignated~~ Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 8-T26S-R27E
12. COUNTY OR PARISH
Eddy
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3201' GR

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☒
☐
☐
☐
☐
☐
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 1970' Anhydrite. Prep to drill ahead. Drilled a 14-3/4" hole to a T.D. of 1970' in Anhydrite. Ran and set 46 jts. (1942') 10-3/4" OD 45.5# casing @ 1967' and cemented w/1125 sacks of Halco Lite w/6# salt + 1/4# Flocele/sack + 200 sacks of Class C w/1/4# + 2%CaCl₂/sack cement. PD @ 0500 MST on 1-4-83. Cement circulated to surface. WOC 18 hrs. Tested 10-3/4" casing to 1500# for 30 min. - OK.

Mr. Cortez w/MMS witnessed cementing job.

RECEIVED
JAN 14 1983

MINERALS MGMT. SERVICE
ROSWELL, NEW MEXICO

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

Prod.

SIGNED Elmer Startz

TITLE Reg. Opr. Mgr. -

DATE 1-12-83

ACCEPTED FOR RECORD (This space for Federal or State office use)

(ORIG. SGD.) **DAVID R. GLASS**

DATE

APPROVED BY
CONDITIONS OF APPROVAL IF ANY:

JAN 14 1983

MINERALS MANAGEMENT SERVICE
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.