

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN 1
(Other, Instru
verse sides.

Form approved.
Budget Bureau No. 42-R1424.

LEASE DESIGNATION AND SERIAL NO.

MM-24777

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "7"

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

WILDCAT DELAWARE

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 14 T-26-S, R-30-E

12. COUNTY OR PARISH 13. STATE

EDDY

NM

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

TOM L. INGRAM

3. ADDRESS OF OPERATOR

P.O. BOX 1757, Roswell, N.M. 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

330' FSL & 760' FWL Sec. 14

14. PERMIT NO.

30-01S-24384

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3122 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/6/87

Surface location cleaned, leveled and re-seeded as per USGS requirements.
(work performed by George Boyse Trucking Co.)

12/12/83-12/19/83

Set CIBP @ 5665' with 35' cement on top.

Set 100' cement plug @ 4560'

Set 100' cement plug @ 3632'

Cut 5 1/2" casing @ 2600' and pulled

Set 150' cement plug 2500-2650'

Set 100' cement plug outside 8 5/8" @ 300-400'

Set 100' cement plug inside 8 5/8" @ 300-400'

Set 50' cement plug @ surface

Mud-laden brine used between plugs

Set dry hole marker

ACCEPTED FOR RECORD

SJS

SEP 4 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

TITLE Engineer

DATE 8/12/87

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

Approved by _____
Working under _____
surface restoration is completed.

*See Instructions on Reverse Side