

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ DRILLING WELL

2. NAME OF OPERATOR
WORTH PETROLEUM COMPANY

3. ADDRESS OF OPERATOR
P.O. BOX 17406, FORT WORTH, TEXAS 76102

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1665' FSL & 330' FEL OF SECTION 27
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

PROGRESS REPORT

RECEIVED BY

SEP 08 1983

O. C. D.
ARTESIA, OFFICE

5. LEASE NM-38636
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME AMOCO FEDERAL
9. WELL NO. 1
10. FIELD OR WILDCAT NAME UNDESIG.
BRUSHY DRAW-CHERRY CANYON
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 27, T. 26 S., R. 29 E.
12. COUNTY OR PARISH EDDY
13. STATE NEW MEXICO
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
2869.1GR.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Perforated 4-1/2" casing 5-17-83 in interval 5350-58, 18 holes. Set packer at 5180. Acidized with 420 gallons. Frac'd with 10,000 gals. and 16,000# sand. Well swabbed down with only a slight show of oil.

Set CIBP 5-23-83 at 5300' with 20 feet of cement on top. Perforated 4969-5039 and squeezed with 200 sacks cement. Drilled out cement to PBTD of 5280. Pressure tested squeezed interval. Tested O.K.

Perforated casing 5-30-83 in intervals 4984-90 and 5000-5004. Acidized perforations with 500 gals acid. Frac'd perforated interval with 16,000 gals. and 24,000# sand.

Well shut in to build tank battery.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Arthur R. Brown TITLE Agent DATE 6-16-83

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 6 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO