0 1070		Form Approved.
Dec. 1973	UNITED STATES	Budget Bureau No. 42-R1424 5. LEASE
5 1985	DEPARTMENT OF THE INTERIOR	NM-18215
C. D.	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
, OFFICE	Y NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use thi	s form for proposals to drill or to deepen or plug back to a differe form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil 📈	gas	Shewell Federal
	weii other DRY	9. WELL NO.
	Corporation V	10. FIELD OR WILDCAT NAME
	S OF OPERATOR Box 1600, Midland, Texas 79702	Wildcat (Delaware)
	ON OF WELL (REPORT LOCATION CLEARLY, See space 1	11. SEC., T., R., M., OR BLK. AND SURVEY OF
below.)	FACE: 660' FNL and 660' FEL of Sec. 10	Sec. 10-268-26E
AT TOP	PROD. INTERVAL:	Eddy New Mexico
	AL DEPTH: APPROPRIATE BOX TO INDICATE NATURE OF NOTIC	14. API NO. E. 33-015-24469
	, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD 3345' GR
ABANDON* (other) 17. DESCRI	BE PROPOSED OR COMPLETED OPERATIONS (Clearly s g estimated date of starting any proposed work. If well i	s directionally drilled, give subsurface locations and
measure	ed and true vertical depths for all markers and zones perti	nent to this work.)*
measure The at	oove well was plugged as follows on M	nent to this work.)*
measur The al	oove well was plugged as follows on M Circulate hole w/9.5# brine	nent to this work.)*
measure The al	oove well was plugged as follows on M	nent to this work.)*
measure The al (S	Dove well was plugged as follows on M Circulate hole w/9.5# brine Spot plug @ 1601-1926' w/35 sx C1C Perf. 690' w/2 shots Spot 220 sx C1C cement down 5 1/2" ca	ay 30, 1984:
The al	oove well was plugged as follows on M Circulate hole w/9.5# brine Spot plug @ 1601-1926' w/35 sx C1C Perf. 690' w/2 shots	ay 30, 1984:
The al	Dove well was plugged as follows on M Circulate hole w/9.5# brine Spot plug @ 1601-1926' w/35 sx C1C Perf. 690' w/2 shots Spot 220 sx C1C cement down 5 1/2" ca cement surfaces out of 8 5/8" annulus	ay 30, 1984:
The al	Dove well was plugged as follows on M Circulate hole w/9.5# brine Spot plug @ 1601-1926' w/35 sx C1C Perf. 690' w/2 shots Spot 220 sx C1C cement down 5 1/2" ca cement surfaces out of 8 5/8" annulus	ay 30, 1984:
The al	Dove well was plugged as follows on M Circulate hole w/9.5# brine Spot plug @ 1601-1926' w/35 sx C1C Perf. 690' w/2 shots Spot 220 sx C1C cement down 5 1/2" ca cement surfaces out of 8 5/8" annulus	ay 30, 1984:
The al	oove well was plugged as follows on M Circulate hole w/9.5# brine Spot plug @ 1601-1926' w/35 sx C1C Perf. 690' w/2 shots Spot 220 sx C1C cement down 5 1/2" ca cement surfaces out of 8 5/8" annulus Install dry hole marker Safety Valve: Manu. and Type	nent to this work.)* ay 30, 1984: JUN 15 sing until Set @ F
The al	Dove well was plugged as follows on M Circulate hole w/9.5# brine Spot plug @ 1601-1926' w/35 sx C1C Perf. 690' w/2 shots Spot 220 sx C1C cement down 5 1/2" ca cement surfaces out of 8 5/8" annulus Install dry hole marker Safety Valve: Manu. and Type	nent to this work.)* ay 30, 1984: JUN 15 sing until Set @ F
The all (Subsurface	Safety Valve: Manu. and Type	nent to this work.)* Image: Set @

; /*

. .

ł

*See instructions on Reverse Side