Form 9-331 Dec. 1973 Dec. 1973 NM OIL CONS. COMMISSION Drawer I Artesia, NM 88210 UNITED STATES	Form Approved. Budget Bureau No. 42-R1424
DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED_BY
SUNDRY NOTICES AND REPORTS ON WEL (Do not use this form for proposals to drill or to deepen or plug back to a d reservoir. Use Form 9–331–C for such proposals.)	LS 7. UNIT AGREEMENT NAME ifferent 8. FARM OR LEASE NAME DEC 14 1983
 oil well X gas well other NAME OF OPERATOR J. C. Williamson 	MWJ Frederal O. C. D. 9. WELL NO. 2 10. FIELD OR WILDCAT NAME Brushy Draw P. change
 ADDRESS OF OPERATOR P. 0. Box 16, Midland, Texas 79702 LOCATION OF WELL (REPORT LOCATION CLEARLY. See spatial below.) AT SURFACE: 660' FNL & 1980' FEL AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same 	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 35 T-26-S, R-29-E12. COUNTY OR PARISH13. STATE Eddy14. COUNTY OR PARISH15. STATE New Mexico
AT TOTAL DEPTH: Same 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NO REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT TEST WATER SHUT-OFF	15. ELEVATIONS (SHOW DF, KDB, AND WD) 2891.4 GR
SHOOT OR ACIDIZE	(NOTE: Report results of multiple completion or zone change on Form 9-330.)

Ő!

1

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well at 1:00 AM 11-11-83

Ran 11 joints of 12-3/4" H-40, Casing set at 373'. Cemented with 375 sx Class "C" 2% CaCl Plud down 2:45 AM. 11-12-83

Subsurface Safety Valve: Manu. and Type	Shaeffer 11" doulbe ram 3000# Set @ 565 Ft
18. Thereby certify that the foregoing is tru	TITLE Production Secretary 10-83
	TITLE I FOULLETOIT SECTE COLDATE
APPROVED BY (ORIG. SGD.) DAVID CONDITIONS OF APPROVALE & 12 1983	
ROSWELL, NEW MEXIC	0 IS a testmetions on Perverse Side

*See Instructions on Reverse Side