	IHL INIERIUR verse alde) MANAGEMENT	5. LEASE DESIGNATION AND BERIAL NO.
RECEIVED SUNDRY NOTICES AND	DEDODTC ON MENT	8. IF INDIAN, ALLOTTEE OR TRIBE NAME
JAN 16 1985 Use "APPLICATION FOR PER	o deepen or plug back to a different reservoir. MIT-" for such proposals.)	ALLOTTEL OR TRIBE NAME
VILO. C. DYELL DOTHER	E THUR MANES	7. UNIT AGREEMENT NAME
2. ARYESTA, OFFICE		8. FARM OR LEASE NAME
J.C. Williamson		HOLLY "A" FEDERAL
P.O. Box 16 Midland, TX 7970		9. WBLL NO.
LOCATION OF WELL (Report location clearly and in according see also space 17 below.)	ordance with any State regardenters	2
At surface	OHer	10. FIELD AND POOL, OZ WILDCAT
1980' FNL & 1980' FWL ¥	A Constant of the second se	BRUSHY DRAW - Delaware 11. ABC., T., B., M., OR BLE. AND SURVEY OR ARRA SEC
4. PERMIT NO.	New Yer	SEC. 26
15. ELEVATIONS	(Show whether DF, RT, GR, etc.)	<u>T-26-S, R-29-E</u> 12. COUNTY OR PARISH 13. STATE
2892.0		EDDY NM
Utteck Appropriate Box	To Indicate Nature of Notice, Report,	or Other Data
NOTICE OF INTENTION TO :	1	BARQUENT REPORT OF :
TEST WATER SHUT-OFF PULL OR ALTER CAS		
FRACTURE TREAT MULTIPLE COMPLET	FRACTURE TREATMENT	ALTEBING CASING
	BHOOTING OR ACIDIZING	ABANDONMENT
(Otber)	(Other) Spud & (Norr: Percet a	surface casing
DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly SI proposed work. If well is directionally drilled, give nent to this work.)*	tate all pertinent datail	sults of multiple completion on Well completion Report and Log form.)
12-16-84 Ran 7 jts. 13 3/8" cash culation @ 260! 340! c	al #2. ing 72 & 77# 8 round casing	to <u>460'</u> . Broke cir-
additives. Top cement @ 25 sx. 35 sx 40 sx 55	al #2.	to <u>460</u> °. Broke cir- casing w/500 sx being Halco lite w/thick set 6 times set plug of
12-16-84 Ran 7 jts. 13 3/8" cash culation @ 260', 340' & 250 sx Class "C", 2% Cau additives. Top cement @ 25 sx, 35 sx, 40 sx, 55 to surface on last plug 35 hereby certify that the foregoing is true and correct HGNED Hill Wills This space for Federal or State office use) PPROVED BY	al #2. ing 72 & 77# & round casing TD. No returns. Cemented Cl ₂ , 1/4# flocel/sx & 250 sx 9 147'. 1" outside 13 3/8", sx, 25 sx, 25 sx and finall as witnessed by BLM represe TITLE <u>Agent</u>	to 460'. Broke cir- casing w/500 sx being Halco lite w/thick set 6 times set plug of Cy circulated cement entative.
12-16-84 Ran 7 jts. 13 3/8" cash culation @ 260', 340' & 250 sx Class "C", 2% Cau additives. Top cement @ 25 sx, 35 sx, 40 sx, 55 to surface on last plug 35 10 surface on last plug 35 This space for Federal or State office use) PPROVED BY ACCOMPTIONS OF APPROVAL, IF ARX: JAN 1 1 1023	al #2. ing 72 & 77# & round casing TD. No returns. Cemented Cl2, 1/4# flocel/sx & 250 sx 9 147'. 1" outside 13 3/8", sx, 25 sx, 25 sx and finall as witnessed by BLM represe TITLE	to 460'. Broke cir- casing w/500 sx being Halco lite w/thick set 6 times set plug of by circulated cement entative.
12-16-84 Ran 7 jts. 13 3/8" cash culation @ 260', 340' & 250 sx Class "C", 2% Cau additives. Top cement @ 25 sx, 35 sx, 40 sx, 55 to surface on last plug 35 10 surface on last plug 35 This space for Federal or State office use) PPROVED BY ACCOMPTIONS OF APPROVAL, IF ARX: JAN 1 1 1023	al #2. ing 72 & 77# & round casing TD. No returns. Cemented Cl ₂ , 1/4# flocel/sx & 250 sx 9 147'. 1" outside 13 3/8", sx, 25 sx, 25 sx and finall as witnessed by BLM represe TITLE	to 460'. Broke cir- casing w/500 sx being Halco lite w/thick set 6 times set plug of by circulated cement will Hair DEG20 1584 DEG20 1584 DEG20 1584 DEG20 1584 DATE 12-18-84