NM OIL CONS. COMMISSION
Drawer DD
Artesia, NM 88210

(Rev. 5-63)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE* (See other instructions on reverse side)

RECEIVED BY
JAN 24 1985
ARTESIA, OFFICE

Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

5. LEASE DESIGNATION AND SERIAL NO.: NM-~~10609~~ 19609

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT AGREEMENT NAME:

1a. TYPE OF WELL: OIL WELL [X] GAS WELL [ ] DRY [ ] Other

b. TYPE OF COMPLETION: NEW WELL [X] WORK OVER [ ] DEEP-EN [ ] PLUG BACK [ ] DIFF. RESVR. [ ] Other

8. FARM OR LEASE NAME: HOLLY "A" FEDERAL

2. NAME OF OPERATOR: J.C. WILLIAMSON

9. WELL NO.: 4

3. ADDRESS OF OPERATOR: P.O. BOX 16 MIDLAND, TEXAS 79701

10. FIELD AND POOL, OR WILDCAT: BRUSHY DRAW DELAWARE

4. LOCATION OF WELL (*Report location clearly and in accordance with any State requirements*)*
At surface: 660' FNL & 660' FWL
At top prod. interval reported below
At total depth: 660' FNL & 660' FWL

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA: Sec. 26, T-26-S, R-29-E

14. PERMIT NO. | DATE ISSUED

12. COUNTY OR PARISH: EDDY | 13. STATE: NEW MEXICO

15. DATE SPUDDED	16. DATE T.D. REACHED	17. DATE COMPL. (*Ready to prod.*)	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*	19. ELEV. CASINGHEAD
12/4/84	01/06/85	01/17/85	2878.0 GR	

20. TOTAL DEPTH, MD & TVD	21. PLUG, BACK T.D., MD & TVD	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
5170'	5131'		→	X	

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*: 4946-5022' DELAWARE

25. WAS DIRECTIONAL SURVEY MADE: see attached

26. TYPE ELECTRIC AND OTHER LOGS RUN: CDL/CNS/GR, DLL/GR, LASERLOG, CEMENT BOND LOG

27. WAS WELL CORED: NO

28. CASING RECORD (*Report all strings set in well*)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
12-3/4"	35#	151'	17-1/2"	250sx Class "C" 2% CaCl	
9-5/8"	36#	486'	12-1/4"	500sx Class "C" 2% CaCl	
7"	23#	2918'	8-3/4"	150sx Class "C" 2% CaCl	
4-1/2"	10.5#	5170'	6-1/4"	150sx Class "C", 150sx Halco Lite	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2-3/8"	5022'	

31. PERFORATION RECORD (*Interval, size and number*): 4946-5022' 21 holes (0.41" in two runs)

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4946-5028'	3000 gal 7-½% NEFE, frac w/53,000 gal. gelled KCl wtr. 93,000# 20-40 sand.

33.* PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (*Flowing, gas lift, pumping—size and type of pump*)	WELL STATUS (*Producing or shut-in*)
01/17/85	Flowing	Producing

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD →	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
01/17/85	24	12/64		300	310	70	1033/1

FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)
400	400		300	310	70	39°

34. DISPOSITION OF GAS (*Sold, used for fuel, vented, etc.*): Sold

TEST WITNESSED BY: Joe Baccus

35. LIST OF ATTACHMENTS: CDL/CNS/GR, DLL/GR, LASERLOG, CEMENT LOG, Request for allowable, Deviation report

ACCEPTED FOR RECORD
JAN 2 1985
NEW MEXICO

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED [signature] TITLE Agent DATE 1/18/85

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.
If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.
Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.
Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.
Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.
Item 29: *"Sacks Cement":* Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.
Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
Surface Triassic	0	20	sand conglomerate and lime
Dewey Lake	20	430	red shale and redsand
Rustler	430	500	anhydrite and lime
Salado	500	1200	salt anhydrite and potash
Castile	1200	2920	anhydrite and salt, some lime
Delaware	2920	2950	lime and shale
Delaware sand	2950	3858	sand and shale, some lime
Cherry Canyon	3858	5205	lime , sand and shale
Brushy Canyon	5205	TD	sand, shale and some lime

38. GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH
Delaware Lime	2910	-27
Delaware Sand	2960	-87
Cherry Canyon	3858	-975
Cherry Canyon Marker	4015	-1832
Brushy Canyon	5205	-2322

*GPO 782-929