

RECEIVED BY
(May 1985)

APR -3 1985

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-23765

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Phillips Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Brushy Draw Del. ~~Ext.~~

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1, T-26S, R-29-E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1. OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

JFG ENTERPRISE

3. ADDRESS OF OPERATOR

P.O. Box 100, Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 660' FEL, Sec. 1, T-26S, R-29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3028' Gr.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Running Prod. Pipe

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-17-85 Drilled out from under 13 3/8" casing with 7 7/8" hole. Reached TD of 6241' on 3-2-85. Circulated hole. Ready to log on 3-3-85. Unable to get log's down. Circulate and improve hole conditioning until 3-5-85.

3-5-85 Laid down drill pipe. Ran 150 jts. 5 1/2" 8-rd LT&C 15.5# J-55 API 6258.40 ft. 5 1/2" Float Shoe, 1 jt. and 5 1/2" Float Collar @ 6226 ft. Ran DV tool @ 4522 ft. First stage 450 sx CL-C with 50/50 poz. with 6# salt, 1/4# Flo Seal; Second Stage 450 sx Class C with 50/50 poz with 6# salt 1/4# Flo Seal; Last Plug down @ 1:45 p.m. 3-6-85.

ACCEPTED FOR RECORD

APR 2 1985

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE 3-21-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side