




P. O. BOX 2267, MIDLAND, TEXAS 79702 (915) 683-4871  
July 18, 1985



Oil Conservation Division  
P. O. Box 2088  
State Land Office Bldg.  
Santa Fe, New Mexico 87501

In: Hay Hollow 25 State #1

Attn: Mr. Joe D. Ramey  
Division Director

Dear Mr. Ramey:

There are several reasons why we feel that completions utilizing a TIW Polish Bore Receptacle or Insert Seal Assembly is the most advantageous method to complete a well.

1. The inside diameter of the seal assembly is the same as the diameter of the tubing. Therefore, there is no restriction that would reduce the size of wireline tools that could be run in the hole.
2. The Polish Bore Receptacle has a full bore opening to the liner below it. This allows us to run bridge plugs, retainers, or bits into the liner if necessary.
3. The seal assembly - PBR hook-up allows for tubing movement while treating the well. It will withstand higher treating pressures during stimulation than would be possible with most other production packers.
4. In most of the wells drilled in this area there are several zones of interest. By having the seal assembly stung into the PBR, the lowest zone can be tested and if non-productive, squeezed. The next zone of interest can then be perforated, acidized and tested. All this can be accomplished without pulling the tubing. This can save a considerable amount of time and money.

The Polish Bore Receptacle is run on the top of the liner. The Insert Seal Assembly sets in the tie back sleeve at the top of the liner.

We feel that this Packer system not only saves us a considerable amount of time and money, but also is the most reliable Packer system available. Of the several hundred wells in which HNG Oil Company has utilized this system over the past years, we have had very few failures. If you have any questions, please feel free to give me a call.

Very truly yours,

George M. Hover  
Petroleum Engineer III

GMH/bg