

458

RECEIVED BY
Form 9-331
Dec. 1973
SEP 11 1985
O. C. D.
ARTESIA, OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR

PERRY R. BASS

3. ADDRESS OF OPERATOR

P.O. BOX 2760, MIDLAND, TX. 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 1980' FWL UNIT LETTER K.

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) 9 5/8" CSG. & CEMENT

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

☒

5. LEASE

NM 031383

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

POKER LAKE UNIT

8. FARM OR LEASE NAME

POKER LAKE UNIT

9. WELL NO.

67

10. FIELD OR WILDCAT NAME

Big Sinks (Narrow)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 3, T25S R31E

12. COUNTY OR PARISH

EDDY

13. STATE

NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3424.1' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DRLD. 12 1/4" HOLE TO 12,000' 9-3-85.

RAN 59 JTS. 9 5/8" 47# 5-95 LT&C, 77 JTS. 43.5# 5-95 LT&C, & 119 JTS. 40# 5-95 LT&C, & 40# N-80 LT&C 15 JTS. 40# N-80 BUTTRESS, & 47# 5-95 LT&C & 16 JTS. 47# 5-95 LT&C CSG. SET @ 12,000'

CEMENTED W/ 700 SX CLASS "H" CEMENT W/ ADDITIVES (15.6 PPg, 1.18 FT 3/4, FLOAT HEAD, PLUG DOWN @ 6:10 P.M. 9-3-85. CALC. TOC 10,600' WOC. 27 3/4 HRS. DRLD. 90' CEMENT, F. COLLAR & SHADE, DRLD. 5' NEW HOLE TESTED CSG. SEAT TO 3500 PSI (15.5 PPg EQUIVALENT) OK.

DRLG. 8 1/2" HOLE 9-5-85

Subsurface Safety Valve: Manu. and Type

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

R.C. [Signature]

TITLE

SR. PROD. CLERK

DATE

SEPT. 6, 1985

(This space for Federal or State office use)

APPROVED BY

ACCEPTED FOR RECORD

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

SWD
SEP 10 1985