

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

Form approved
Budget Bureau No. 1004-0155
Expires August 31, 1985

ckf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER


2. NAME OF OPERATOR
LaRue and Muncy

3. ADDRESS OF OPERATOR
P.O. Box 1262, Artesia, NM 88211-2602

4. LOCATION OF WELL (Report location clearly and to accordance with all instructions on back of this form.)
See also space 17 below)
At surface
3044' GL

5. ELEVATION (Show whether in ft. or m. etc.)
3044' GL

6. UNIT AGREEMENT NAME
(Unit I.)
(NW1SW1)



5. LEASE DESIGNATION AND SERIAL NO.
NM-16814

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Bedena Federal

9. WELL NO.
#1

10. FIELD AND POOL OR WILDCAT
E. Brushy Draw Del Norte

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Sec. 18: T-26S, R-30E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENT TO		SUBSEQUENT REPORT OF:	
WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACURE TREATMENT	☐	FRACURE TREATMENT	☒
SHOOTING OR ACIDIZING	☐	SHOOTING OR ACIDIZING	☒
REPAIR WELL	☐	REPAIR WELL	☐
REPAIR OR ALTER CASING	☐	REPAIR OR ALTER CASING	☐
REPAIR OR ALTER PACKER	☐	REPAIR OR ALTER PACKER	☐
REPAIR OR ALTER VALVE	☐	REPAIR OR ALTER VALVE	☐
REPAIR OR ALTER PUMP	☐	REPAIR OR ALTER PUMP	☐
REPAIR OR ALTER TUBING	☐	REPAIR OR ALTER TUBING	☐
REPAIR OR ALTER CEMENT	☐	REPAIR OR ALTER CEMENT	☐
REPAIR OR ALTER OTHER	☐	REPAIR OR ALTER OTHER	☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 2/18/86 Squeezed perforations at 5373-5446 with 150 sks Class "H" with 2% gel and 150 gals flocheck
- 2/19/86 Drilled cement retainer and cement to 5446', Circulated hole at 6120
- 2/21/86 Ran cement bond log and evaluated
- 2/22/86 Hydrojet 6100, 5408 with 2 cuts per foot, acidized with 500 gals 15% NEFE HCL. Swabbed with packer set at 5950', swabbed acid water
- 2/23/86 Swabbed formation water with trace of oil and gas
- 2/24/86 Set CIBP at 5980', hydrojet 5291, 5358, 5372 with 2 cuts per foot, acidized with 1500 gals 15% NEFE HCL. Swabbed acid water with packer set at 5250'
- 2/25/86 Swabbed formation water with trace of oil and gas.
- 2/26/86 Bridge plug set at 3850', hydrojet 3321, 29.45 with 2 cuts per foot, acidized with 1000 gals 15% NEFE HCL and 500 gals 15% HF acid, swabbed acid water with packer set at 3250'
- 2/27/86 Swabbed formation water with trace of oil and gas, run tubing and rods. Hung on pump. Total tubing 3352 of 2 7/8", SN at 3319
Pump testing Ramsey, Water production trucked to disposal wells.

I hereby certify that the foregoing is true and correct

APPROVED BY Dickie Jue TITLE Production Clerk DATE 4/8/86

(Leave space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY SWD TITLE SWD DATE APR 14 1986

*See Instructions on Reverse Side

CAPISBAD, NEW MEXICO