

November 1984
(Populate 1985)

RECEIVED BY DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SEP 19 1985

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

O. C. D.

1. NAME OF OPERATOR
Earle M. Craig, Jr. Corporation

2. ADDRESS OF OPERATOR
P. O. Box 1351, Midland, Texas 79702-1351

3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
1970' FNL and 670' FEL of Section 19

4. PERMIT NO.
30-015-25299

5. ELEVATIONS (Show whether BP, SP, GR, etc.)
3183' GR

6. LEASE DESIGNATION AND SERIAL NO.
NM-0459862-A

7. IF INDIAN, ALLOTTEE OR TRIBE NAME

8. UNIT AGREEMENT NAME

9. FARM OR LEASE NAME
Spitfire "19"

10. WELL NO.
1

11. FIELD AND POOL, OR WILDCAT
Undesignated
Phantom Draw Well

12. SEC., T., R., OR BLK. AND
SUEVEY OR AREA
Sec. 19, T-26-S,
R-31-E

13. COUNTY OR PARISH
Eddy

14. STATE
New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANT

(Other) Set 9 5/8" csg and cement

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. REPORT OF OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1) 10 June 85 - Cont'd drlg 12 1/4" hole -(2223' to 3820')
thru
16 June 85

17 June 85

2) T.D. 3820' - Ran 92 total jts (3826.59') 9 5/8" casing - 9 jts. (384.82') 9 5/8" 36#/ft, S-80, ST&C and 83 jts (3441.77') 36#/ft, K-55, ST&C. Casing landed at 3820' K.B. cemented w/2000 sxs Pacesetter Lite w/3% salt and 1#/sz Hiseal plus 250 sxs Class "C" cement. Plug down at 1:30 a.m. 16 June 85. Circulated 150 sxs excess cement.

I hereby certify that the foregoing is true and correct

James E. Kelly

TITLE Mgr, Drlg & Prod

DATE 10 Sept 85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

SEP 11 1985

*See Instructions on Reverse Side