

SEP 19 1985 SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.)

1. JAMES H. OFFICE
2. NAME OF OPERATOR
Earle M. Craig, Jr. Corporation
3. ADDRESS OF OPERATOR
P. O. Box 1351, Midland, Texas 79702-1351
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

7. UNIT AGREEMENT NAME
8. FIRM OR LEASE NAME
Spitfire "19"
9. WELL NO.
1
10. FIELD AND POOL, OR WILDCAT
Undesignated
Phantom Draw No
11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

1970' FNL and 670' FBL of Section 19

14. PERMIT NO. 30-015-25299
15. ELEVATIONS (Show whether IN, ON, OR, OUT)
3183' GR

Sec. 19, T-26-S,
R-31-E
12. COUNTY OR PARISH Eddy
13. STATE New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF
FRACTURE TREAT
SUGGET OR ACIDIZE
REPAIR WELL
(Other)

PULL OR ALTER CASING
MULTIPLE COMPLETION
ABANDONMENT
CHANGED LEASE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF
FRACTURE TREATMENT
SUGGETING OR ACIDIZING
(Other) Set 4 1/2" csg & cmt
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL
ALTERING CASING
ABANDONMENT*

17. If well is abandoned or completed, operator must clearly state all pertinent details and give pertinent dates, including estimated date of starting any future work. If well is abandoned, operator must give subsurface locations and measured and true vertical depths for all markers and zones pertinent to the work.

- 1) 11 August 85 - T. D. 12,927' - Ran 4 1/2" production csg as follows:
from top: 59 jts 2454.87', 4 1/2", 11.60#, N-80 Buttress
156 jts 7061.02', 4 1/2", 11.60#, N-80 LT&C
85 jts 3422.95', 4 1/2", 11.60#, S-95, LT&C

Ruff coated three sections of casing and centralized btm 600'.

12,413.85' - 12,536.16'
12,575.87' - 12,616.44'
12,657.44' - 12,695.61'

Casing landed at 12,937.32' with 126,000# tension.

Cemented w/450 sxs C1 "H" cmt w/1.25% flolock, .1% LWS, .2% AFS.
Plug down at 4:00 a.m. 11 August 1985.

I hereby certify that the foregoing is true and correct

SIGNED James E. Guley
(This space for Federal or State office use)

TITLE Mgr, Drlg & Prod

DATE 10 Sept 85

APPROVED BY
CONDITIONS OF APPROVAL IF ANY:

TITLE

DATE

SEP 17 1985

*See Instructions on Reverse Side