

RECEIVED BY

JAN 24 1986

O. C. D.  
ARTESIA, OFFICE

UNITED STATES

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

Budget Bureau No. 42-R1424

c/5F

## SUNDY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☒ Dry Hole

2. NAME OF OPERATOR

Flag-Redfern Oil Company ✓

3. ADDRESS OF OPERATOR

P.O. Box 11050 / Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL and 660' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☒

(other)

SUBSEQUENT REPORT OF:

☐☐☐☐☐☐☐☒☐

5. LEASE

NM 27649

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sun "10" Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

East brushy draw Del

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10 T-26-S R-30-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

30-015-25298

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3125

KDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

7-25-85 Set CIBP at 3620'. Spotted 40 sx class "C" cement from 3620' to 3220'.

7-26-85 Tagged TOC at 3193'. Loaded hole with mud laden fluid. Shot 5½" casing off at 2540'. Layed down 60 jts casing. Spotted 20 sx class "C" from 2590' to 2447'. Spotted 30 sx class "C" cement from 1950' to 1840'. Spotted 30 sx class "C" cement from 655' to 545'. Spotted 15 sx class "C" from 50' to surface.

7-27-85 Cut casing off and installed dry hole marker.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Kelly J. Jansen

TITLE

Engineer

DATE

8-10-85

(This space for Federal or State office use)

APPROVED BY

Mark H. Hester

TITLE

DATE

1-21-86

CONDITIONS OF APPROVAL, IF ANY: