

GEOLOGICAL SURVEY

NM-15302

RECEIVED BY
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL ☒ GAS ☒
WELL ☒ OTHER ☐

2. NAME OF OPERATOR
ARTESIA, OFFICE

(Bill Cozart)

(915-682-5218)

3. ADDRESS OF OPERATOR

611 Petroleum Building, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2310' FNL & 660' FEL of Section

(Unit H)

(SE 1/4 NE 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, RT, GR, etc.)

2925.5' GR

2944.5' KB

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gulf Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat - Penn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 5, T25S, R29E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Running 10-3/4" int. csg.

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Drilled 14-1/2" hole and set 10-3/4", 40.5# & 45.5#, K-55, STC casing at 2650' KB. Cemented with 1175 sacks Halliburton Lite plus 6# salt and 1/4# flocele per sack, followed by 250 sacks Class "C" plus 2% CaCl. Circulated 145 sacks to pit 7-1-85.
2. Installed 10" 5M casing head flange and 10" 5M blowout preventer.
3. Pressure tested blowout preventers and casing to 1000#.
4. After WOC 24 hours, started drilling 9-1/2" hole 7-3-85.

18. I hereby certify that the foregoing is true and correct

SIGNED B.W. Cozart (B.W. Cozart)

TITLE Drilling Foreman

DATE 7-3-85

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JUL 12 1985

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO