

(November 1983)
(Formerly 9-331)

RECEIVED BY DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

DEC - SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

O.C.D.

ARTESIA OFFICE

1. NAME OF OPERATOR

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

2260' FSL & 2310' FWL of Sec. 22

(Unit K)

(NE 1/4 SW 1/4)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RL, GR, etc.)

2895.9 2891.9 GL

Expires August 31, 1985

COMMISSION

LEASE DESIGNATION AND SERIAL NO.

NM-22634

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mobil "22" Federal

9. WELL NO.

#6

10. FIELD AND POOL, OR WILDCAT

Undr
Brushy Draw - Delaware

11. SEC., T., R., OR BLK. AND
SURVEY OR AREA

Sec. 22, T-26-S, R-29-E

12. COUNTY OR PARISH 13. STATE

Eddy

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PAVE OR ALTER CASING

FRAC. AND TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZING

ABANDON*

REPAIR WELL

CHANGE PLANT

OTHER

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRAC. TREATMENT

SHOOTING OR ACIDIZING

(Other)

Cement & casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. OTHER UNFINISHED OR COMPLETED OPERATION. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
production work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

11-5-85

Well was spudded 9:30 am

Rn 363' of 8 5/8", 23# casing

Cemented with 235 sks Class "C", 3% CaCl, 1/4# flocele

Plug down 11:15 pm - 11/5/85

Did not Circulate

Stage cemented 250 sks Class "C" neat, 4% CaCl, Circulated 10 sks

Pressure tested 200# for 30 minutes - Held, WOC 18 hours.

11/16/85

Well was drilled to a total depth of 6213'

Ran 6223' of 5 1/2", 15.5# J55

Cemented (first stage) 225 sks Class "H", 6# salt, 1/4# flocele, 3/10% Hallard #4,
2/10% CFR-3, Plug down 8 am, 11-18-85, WOC 4 hours

Cemented (second stage) 325 sks Halliburton Lite, 8# salt, 1/4# flocele, and
400 sks Class "H", 6# salt, 1/4# flocele, 3/10% Hallard #4, 2/10% CFR-3

Plug down 1:15 pm, 11/18/85, Pressured tested 2500# - Held, WOC 5 days

18. I hereby certify that the foregoing is true and correct

SIGNED

Dickie Seal

TITLE Production Clerk

DATE 11/26/85

19. Space for Federal or State office use

APPROVED BY

FOR RECORD

CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

NOV 27 1985

*See Instructions on Reverse Side