

HANSON OPERATING CO., INC.
N. MASON NO. 17

DATE : 11-4-85
FORMATION : CHERRY CANYON

FILE NO. : 32020-14965
API WELL NO.:

CONVENTIONAL PLUG ANALYSIS

SAMPLE NUMBER	DEPTH FEET	PERM MAXIMUM	FLD POR	OILX POR	WTRZ POR	GRAIN DEN M	DESCRIPTION
26	5670.0-71.0	5.4	12.7	11.9	35.6		SD
27	5671.0-72.0	7.6	13.7	10.9	35.6		SD
28	5672.0-73.0	3.1	14.2	10.6	40.9		SD
29	5673.0-74.0	1.4	13.0	7.3	46.6		SD
30	5674.0-75.0	276.0	13.3	7.2	46.2		SD HF
31	5675.0-76.0	1.4	12.9	7.4	47.1		SD
32	5676.0-77.0	1.3	12.4	3.8	50.8		SD
33	5677.0-78.0	1.4	12.1	7.8	40.6		SD
34	5678.0-79.0	1.5	12.4	7.7	41.3		SD
35	5679.0-80.0	2.0	12.6	7.5	42.1		SD
36	5680.0-81.0	3.2	14.0	13.4	38.9		SD
37	5681.0-82.0	3.2	13.5	11.2	39.1		SD
38	5682.0-83.0						NA SD
39	5683.0-84.0	3.9	17.7	3.6	60.3		SD
	5684.0-85.0	4.8	18.4	7.9	52.4		SD
	5685.0-90.0						NA SD
	5690.0-91.0						NA SD LMY
	5691.0-92.0						NA SD SL/LMY
40	5692.0-93.0	0.02	7.6	31.5	52.6		SD
	5693.0-94.0						NA SD SL/LMY
41	5694.0-95.0	<0.01	8.2	24.1	57.9		SD
42	5695.0-96.0	0.01	6.8	23.5	58.8		SD
	5696.0-98.0						NA SD SLTY
	5698.0-1.0						NA SD SL/LMY
43	5701.0-2.0	0.17	10.5	14.8	51.7		SD
44	5702.0-3.0	0.19	12.3	5.5	53.1		SD
	5703.0-5.0						NA SD SL/LMY
	5705.0-6.0						NA SD LMY
	5706.0-9.0						NA SD SL/LMY
	5709.0-12.0						NA SD LMY