

HANSON OPERATING CO., INC.
N. MASON NO. 17

DATE : 11-4-85
FORMATION : CHERRY CANYON

FILE NO. : 32020-14965
API WELL NO.:

CONVENTIONAL FLUG ANALYSIS

SAMPLE NUMBER	DEPTH FEET	PERM MAXIMUM	FLD POR	OIL% POR	WTR% POR	GRAIN DEN M	DESCRIPTION
6	5641.0-42.0	0.03	8.0	8.6	64.0		SD SHLAM
7	5642.0-43.0	0.09	9.7	13.1	50.5		SD SHLAM
	5643.0-44.0						NA SD SHLAM
	5644.0-45.0						NA SD LMY SHLAM
	5645.0-49.0						NA SD SL/LMY SHLAM
8	5649.0-50.0	0.33	10.7	1.8	58.2		SD SHLAM
9	5650.0-51.0	0.16	6.0	3.4	75.6		SD
10	5651.0-52.0	3.0	14.1	6.6	45.1		SD
11	5652.0-53.0	9.2	13.4	6.4	46.7		SD
12	5653.0-54.0	1.0	11.3	3.4	51.4		SD
13	5654.0-55.0	0.15	6.2	3.3	69.0		SD
14	5655.0-56.0	30.	19.3	12.5	41.8		SD SHLAM
15	5656.0-57.0	0.03	10.7	15.0	69.1		SD VF SHLAM
16	5657.0-58.0	1.1	12.8	3.0	55.2		SD VF
17	5658.0-59.0	2.7	15.8	7.6	47.1		SD
18	5659.0-60.0	5.3	15.7	5.9	46.9		SD F
	5660.0-61.0						LOST CORE
CORE NO. 3 5661.0-5722.0 CUT 61' REC 60'							
19	5661.0-62.0	2.1	15.7	9.5	49.8		SD
20	5662.0-63.0	1.5	14.4	6.5	50.8		SD
21	5663.0-64.0	2.3	16.2	11.5	47.0		SD
	5664.0-65.0						NA SD
22	5665.0-66.0	1.9	15.4	4.3	52.2		SD
23	5666.0-67.0	1.9	15.7	7.7	49.9		SD
	5667.0-68.0						NA SD SL/LMY
24	5668.0-69.0	8.5	15.6	14.2	40.4		SD
25	5669.0-70.0	16.	15.8	13.9	34.8		SD